

NEW

75 Ω Miniature Coaxial Connectors with Push-Pull Lock

PL76 Series



Rated at 75 Ω and 3.2 GHz

●Size Comparison with BNC




Fig.①

■Features

1. Miniature 75 Ω Push-Pull Lock

Features Hirose's unique positive locking system

2. Top-Touch Mechanism

The top touch mechanism imparts a high degree of precision for reliably matching each side of the connection.

3. 40% downsized compared with BNC type connectors

The diameter is reduced by approx 40%. (See Fig. ①.)

4. Suited for FA cameras using a 75 Ω design


Accepts a 75 Ω impedance, 3.2 GHz bandwidth and 1 A of current

5. RoHS Compliant

All materials and substances used to produce these parts fully comply with RoHS standards.

●Mating Operation

No tool is required to mate or un-mate this connector. The outer shell has a smooth function and creates an easy push-pull operation.



●Positive Lock

The positive lock will not release unless the outer shell is dis-engaged.




Fig.②

■Mating Diagram

Plug Side

■Straight Plug
PL76-P-2.5CV

Receptacle Side

■Bulkhead Receptacle
PL76-BR-PC
PL76-BR-PC-1

Adapter side


■PL76-HFL Conversion Adapter
PL76J-H.FLJ-BPA
PL76J-H.FLJ-BPA-1

Product Specifications

Ratings	Characteristic impedance : 75 Ω Frequency Rating : DC to 3.2 GHz Current Rating : 1 A	Operating Temp. Range: -30 to +85°C Operating Humid. Range: 95% or less
---------	---	--

Items	Specifications	Conditions
1. Contact resistance	Center: 15 mΩ Max. Outer: 4 mΩ Max.	Measured at 100 mA or less
2. Insulation resistance	Minimum of 1,000 MΩ	Measured at DC 250 V
3. Withstand voltage	No flashover or breakdown	Apply AC 500 V for 1 minute
4. Voltage standing wave ratio(VSWR)	Maximum of 1.3	DC to 3.2 GHz
5. Durability	Contact resistance Center: 19 mΩ Max. Outer: 10 mΩ or less. No breakage, cracks or loose parts	500 mating cycles
6. Vibration resistance	No electric outage of 1μs or more No magnetic field, cracks or loose parts	10 cycles in each of the 3 axes at a frequency of 10-500 Hz, half amplitude 0.75 mm and acceleration 196 m/s ²
7. Shock resistance	No electric outage of 1μs or more No breakage, cracks or loose parts	Acceleration 490 m/s ² , duration 11 ms, half-sine wave, 3 times each for 3 axial directions
8. Moisture-resistance Temperature-humidity cycles	Insulation resistance: Minimum of 10 MΩ (high humidity) Insulation resistance: Minimum of 100 MΩ (low humidity) No breakage, cracks or loose parts	Temperature -10 to 65°C, humidity 90 to 96 % 10 cycles (240 hours)
9. Temperature cycles	No breakage, cracks or loose parts	Temperature: -30°C → → +85°C → -°C Time: 30 min → 3 min → 30 min → 3 min 5 cycles
10. Salt water spray	No significant corrosions	Continuous 48 hours with 5 % salt water

* Measurement system for Voltage Standing Wave Ratio (VSWR)
 Specification values of VSWR above are those measured on the measurement system set up in the diagram below.



Materials

Item	Materials	Finish
Shell	Brass	Nickel plating
Insulation	PTFE	-
Male Contact	Brass	Gold plating
Female Contact	Phosphorous bronze	Gold plating

Product Number Structure


Refer to the chart below for determining specific part number characteristics.
 Please select connectors listed in this catalog when placing orders and be sure to check the latest delivery specifications at the time of ordering the product.

PL76 - [] - []

① ② ③


① Series name: PL76
② Connector type P : Straight Plug BR : Bulkhead Receptacle
③ Applicable cables or mounting styles 2.5CV : 2.5C-2V PC : DIP mount to PCB

■ Plug




Part No.	HRS No.	Applicable Cables	RoHS
PL76-P-2.5C V	CL334-0087-0	2.5C-2V	○

■ Receptacle



Part No.	HRS No.	Nut Style	RoHS
PL76-BR-PC	CL334-0085-5	Spanner	○
PL76-BR-PC-1	CL334-0086-8	Hexagonal	○

■ Conversion Adapter



Part No.	HRS No.	Nut Style	RoHS
PL76J-H.FLJ-BPA	CL311-0470-2	Spanner	○
PL76J-H.FLJ-BPA-1	CL311-0471-5	Hexagonal	○

Sep. 1..2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

Scheduled to be discontinued

USA:

HIROSE ELECTRIC (U.S.A.), INC. Headquarters
 2688 Westhills Court, Simi Valley, CA 93065-6235
 Phone : +1-805-522-7958
 Fax : +1-805-522-3217
<http://www.hiroseusa.com>

USA:

HIROSE ELECTRIC (U.S.A.), INC. San Jose Office
 3255 Scott Boulevard, Building 7, Suite 101
 Santa Clara, CA 95054
 Phone : +1-408-253-9640
 Fax : +1-408-253-9641
<http://www.hiroseusa.com>

USA:

HIROSE ELECTRIC (U.S.A.), INC. Detroit Office (Automotive)
 37677 Professional Center Drive, Suite #100C
 Livonia, MI 48154
 Phone : +1-734-542-9963
 Fax : +1-734-542-9964
<http://www.hiroseusa.com>

THE NETHERLANDS:

HIROSE ELECTRIC EUROPE B.V.
 Hogehillweg #8 1101 CC Amsterdam Z-O
 Phone : +31-20-6557460
 Fax : +31-20-6557469
<http://www.hiroseeurope.com>

GERMANY:

HIROSE ELECTRIC EUROPE B.V. German Branch
 Herzog-Carl-Strasse 4 D-73760 Ostfildern
 (Scharnhauser Park)
 Phone : +49-711-4560-02-1
 Fax : +49-711-4560-02-299
<http://www.hirose.de>

UNITED KINGDOM:

HIROSE ELECTRIC EUROPE B.V. UK Branch
 22 Vincent Avenue, Crownhill Business
 Centre, Crownhill, Milton Keynes, MK8 0AB
 Phone : +44-1908-305750
 Fax : +44-1908-305768
<http://www.hirose.co.uk>

CHINA:

HIROSE ELECTRIC TRADING (SHANGHAI) CO., LTD.
 1601, Henderson Metropolitan, NO.300, East Nanjing
 Road, Huangpu District, Shanghai, China 200001
 Phone : +86-21-6391-3355
 Fax : +86-21-6391-3335
<http://www.hirose-china.com.cn>

CHINA:

HIROSE ELECTRIC TRADING (SHANGHAI) CO., LTD. Beijing Branch
 A1001, Ocean International Center, Building 56# East 4th
 Ring Middle Road, Chao Yang District, Beijing, 100025
 Phone : +86-10-5165-9332
 Fax : +86-10-5908-1381
<http://www.hirose-china.com.cn>

CHINA:

HIROSE ELECTRIC TECHNOLOGIES (SHENZHEN) CO., LTD.
 Room 09-13, 19/F, Office Tower Shun Hing Square, Di Wang Commercial Centre
 5002, ShenNanDong Road, ShenZhen City, Guangdong Province, 518008
 Phone : +86-755-8207-0851
 Fax : +86-755-8207-0873
<http://www.hirose-china.com.cn>

HONG KONG:

HIROSE ELECTRIC HONGKONG TRADING CO., LTD.
 Room 1001, West Wing, Tsim Sha Tsui Centre, 66
 Mody Road, Tsim Sha Tsui East, Kowloon, Hong Kong
 Phone : +852-2803-5338
 Fax : +852-2591-6560
<http://www.hirose-hongkong.com.hk>

TAIWAN:

HIROSE ELECTRIC TAIWAN CO., LTD.
 103 8F, No.87, Zhengzhou Rd., Taipei
 Phone : +886-2-2555-7377
 Fax : +886-2-2555-7350
<http://www.hirose-taiwan.com.tw>

KOREA:

HIROSE KOREA CO., LTD.
 1261-10, Jeongwhang-Dong, Shihung-City,
 Kyunggi-Do 429-450
 Phone : +82-31-496-7000, 7124
 Fax : +82-31-496-7100
<http://www.hirose.co.kr>

SINGAPORE:

HIROSE ELECTRIC SINGAPORE PTE. LTD.
 10 Anson Road #26-1 International Plaza
 079903
 Phone : +65-6324-6113
 Fax : +65-6324-6123
<http://www.hirose-singapore.com.sg>

INDIA:

HIROSE ELECTRIC SINGAPORE PTE. LTD. Bangalore Liaison office
 Unit No.05, Ground Floor, Explorer Building International Tech
 Park Whitefield Road, Bangalore 560066 Karnataka, India
 Phone : +65-6324-6113
 Fax : +65-6324-6123
<http://www.hirose-singapore.com.sg>

INDIA:

HIROSE ELECTRIC SINGAPORE PTE. LTD Delhi Liaison Office
 Suite No. 606 5th Floor SB Tower 1A/1 Sector
 16 A Filmcity Noida 201301 Uttar Pradesh-India
 Phone : +91-120-4804917
 Fax : +91-120-4804949
<http://www.hirose.com/sg/>

MALAYSIA:

HIROSE ELECTRIC SINGAPORE PTE. LTD (Representative office)
 1-10-07, Suntech @ Penang Cybercity (1164), Lintang
 Mayang Pasir 3, 11950, Bayan Baru, Penang, Malaysia.
 Phone : +604-619-2564
 Fax : +604-619-2574
<http://www.hirose.com/sg/>



HIROSE ELECTRIC CO., LTD.

6-3, Nakagawa Chuoh-2-Chome, Tsuzuki-Ku, Yokohama-Shi 224-8540, JAPAN
 TEL: +81-45-620-3526 Fax: +81-45-591-3726
<http://www.hirose.com>
<http://www.hirose-connectors.com>