

SR240-DPE

- 2 Connections



PTR

Phoenix Mecano Brand

Technical Data

Wire sizes		Insulating Material	
Solid min	70.0 mm ²	Material	PA 6.6
Solid max	240.0 mm ²	Flammability Class	UL 94 V-2
Stranded (flexible) min	70.0mm ²	Temperatures	
Stranded (flexible) max	240.0 mm ²	Working Temperature	-40 - 105 °C
Stranded (flexible) min	70.0mm ²	Dimensions	
Stranded (flexible) max	240.0 mm ²	Stripped Length	38.0 mm
Stranded with Ferrule min	70.0 mm ²	Width	36.0 mm
Stranded with Ferrule max	240.0 mm ²	Length	93.0 mm
Clamping Range min	50.0mm ²	Height TS35 x 7.5	126.3 mm
Clamping Range max	240.0 mm ²	Height TS32	132.0 mm

Colours

 BLACK/YELLOW

Connection Diagram



Order Data

Article Designation	Article Number	PU
SR240-DPE-BLACK/YELLOW	41570.2	5

Accessoires

Article Designation	Article Number	PU
External Cross-Connector insulated AQI2/240	492769.2	5
External Cross-Connector insulated AQI3/240	492770.2	5
Covers AD1/240/B	492808.0	20
Einlegprofile EP240	492360.0	10
End Stopn ES35/K/ST	492828.0	50
Quick Labelling PSB6/50	494702.7	500

Ratings

Ratings	UR	CSA	IEC
Rated Voltage	600 V	600 V	1000 V
Rated Current	370 A	370 A	380 A
Rated Wire Size	AWG 500-2/0	AWG 500-2/0	240.0 mm ²
Rated Impulse Voltage			8 V
Pollution Degree			3