

	1	2	3	4	5	6	7																																																																																																	
A					Technical specifications: Materials: 1. Insulator: Glass-Filled PBT, Color: Grey, UL 94V-0 2. Contact: Copper Alloy Contact plating according DIN41612 performance classes: Performance class I (-1) 500 mating cycles min. 30u" AU plating on mating area, Gold Flash on non-mating area, 50u" Nickel underplating 100u" Sn plating on solder area over 50u" Nickel Performance class II (-2) 250 mating cycles min. 15u" AU plating on mating area, Gold Flash on non-mating area, 50u" Nickel underplating 100u" Sn plating on solder area over 50u" Nickel Performance class III (blank) 50 mating cycles min. Gold flash on mating side over 50u" Nickel 100u" Sn plating on solder area over 50u" Nickel Other specifications: Contact resistance: 20mOhm max. Insulation resistance: 10¹²Ohm min. Current rating: 2A Operating temperature: -40°C to 105°C Operating voltage: 125VAC Test voltage: 1000VAC Packaging: Tray			A																																																																																																
B								B																																																																																																
C								C																																																																																																
D								D																																																																																																
E	Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05)				<table><tr><th colspan="12">DIN41612 STYLE HALF C MALE RIGHT-ANGLE</th></tr><tr><th colspan="8">ORDERING CODE</th><th colspan="4">CONTACT DETAILS</th></tr><tr><th></th><th>Style</th><th>M=Male F=Female</th><th>No of pins</th><th>Rows loaded</th><th>Pin type</th><th>Plating Class</th><th>Board lock</th><th>Pin length in mm</th><th>Cross section</th><th>Pin load</th><th>Pin type/direction</th></tr><tr><td>A -</td><td>HC</td><td>M</td><td>xx</td><td>xx</td><td>x</td><td>-</td><td>x</td><td>x</td><td></td><td></td><td></td></tr><tr><th colspan="12">Options (if another contact loading option is needed, please contact your sales office)</th></tr><tr><td>A -</td><td>HC</td><td>M</td><td>48</td><td>abc</td><td>R</td><td>-</td><td>1</td><td>MC1</td><td>R:</td><td>3.00 (±0.25)</td><td>0.60x0.60(±0.03)</td></tr><tr><td></td><td></td><td></td><td>32</td><td>a+c</td><td></td><td></td><td>2</td><td>blank</td><td></td><td></td><td>abc: 3x16 a+c: 2x16 a: 1x16</td></tr><tr><td></td><td></td><td></td><td>16</td><td>a</td><td></td><td></td><td>blank</td><td></td><td></td><td></td><td>THT right-angle</td></tr></table>			DIN41612 STYLE HALF C MALE RIGHT-ANGLE												ORDERING CODE								CONTACT DETAILS					Style	M=Male F=Female	No of pins	Rows loaded	Pin type	Plating Class	Board lock	Pin length in mm	Cross section	Pin load	Pin type/direction	A -	HC	M	xx	xx	x	-	x	x				Options (if another contact loading option is needed, please contact your sales office)												A -	HC	M	48	abc	R	-	1	MC1	R:	3.00 (±0.25)	0.60x0.60(±0.03)				32	a+c			2	blank			abc: 3x16 a+c: 2x16 a: 1x16				16	a			blank				THT right-angle	E
DIN41612 STYLE HALF C MALE RIGHT-ANGLE																																																																																																								
ORDERING CODE								CONTACT DETAILS																																																																																																
	Style	M=Male F=Female	No of pins	Rows loaded	Pin type	Plating Class	Board lock	Pin length in mm	Cross section	Pin load	Pin type/direction																																																																																													
A -	HC	M	xx	xx	x	-	x	x																																																																																																
Options (if another contact loading option is needed, please contact your sales office)																																																																																																								
A -	HC	M	48	abc	R	-	1	MC1	R:	3.00 (±0.25)	0.60x0.60(±0.03)																																																																																													
			32	a+c			2	blank			abc: 3x16 a+c: 2x16 a: 1x16																																																																																													
			16	a			blank				THT right-angle																																																																																													
F								F																																																																																																
G	RoHS compliant Unit:mm		Scale	Free				Date	Name	Description: DIN 41612		G																																																																																												
TOLERANCE						Drawn	30.08.2012	Amy	Type Half C / Male / R/A																																																																																															
X.			±X				Approved	17.08.2020	Winnie	ASSMANN WSW-No.																																																																																														
X.X			±0.40							A-HCMxxxxx-xxx																																																																																														
X.XX			±0.25	②	Change to new plant	17.08.2020	Winnie																																																																																																	
X.XXX			±0.15	①	Update dimension & plating	13.11.2019	Carson			Drawing-No.		ASS 4948 CO	rev02	H																																																																																										
		①	Drawn	30.08.2012	Amy	Customer-No.					SHEET 3 / 4																																																																																													
H		Angle	±3°	Id.	Modification	Date	Name																																																																																																	
	1	2	3	4	5	6	7			SV4824																																																																																														

	1	2	3	4	5	6	7																																																																																																														
A					Technical specifications: Materials: 1. Insulator: Glass-Filled PBT, Color: Grey, UL 94V-0 2. Contact: Copper Alloy Contact plating according DIN41612 performance classes: Performance class I (-1) 500 mating cycles min. 30u" AU plating on mating area, Gold Flash on non-mating area, 50u" Nickel underplating 100u" Sn plating on solder area over 50u" Nickel Performance class II (-2) 250 mating cycles min. 15u" AU plating on mating area, Gold Flash on non-mating area, 50u" Nickel underplating 100u" Sn plating on solder area over 50u" Nickel Performance class III (blank) 50 mating cycles min. Gold flash on mating side over 50u" Nickel 100u" Sn plating on solder area over 50u" Nickel Other specifications: Contact resistance: 20mOhm max. Insulation resistance: 10¹²Ohm min. Current rating: 2A Operating temperature: -40°C to 105°C Operating voltage: 125VAC Test voltage: 1000VAC Packaging: Tray			A																																																																																																													
B									B																																																																																																												
C									C																																																																																																												
D									D																																																																																																												
E	Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05)					<table><tr><th colspan="12">DIN41612 STYLE HALF C MALE RIGHT-ANGLE</th></tr><tr><th colspan="8">ORDERING CODE</th><th colspan="4">CONTACT DETAILS</th></tr><tr><th></th><th>Style</th><th>M=Male F=Female</th><th>No of pins</th><th>Rows loaded</th><th>Pin type</th><th>Plating Class</th><th>Board lock</th><th>Pin length in mm</th><th>Cross section</th><th>Pin load</th><th>Pin type/direction</th></tr><tr><td>A -</td><td>HC</td><td>M</td><td>xx</td><td>xx</td><td>x</td><td>-</td><td>x</td><td>x</td><td></td><td></td><td></td></tr><tr><th colspan="12">Options (if another contact loading option is needed, please contact your sales office)</th></tr><tr><td>A -</td><td>HC</td><td>M</td><td>48</td><td>abc</td><td>R</td><td>-</td><td>1</td><td>MC1</td><td>R:</td><td>3.00 (±0.25)</td><td>0.60x0.60(±0.03)</td></tr><tr><td></td><td></td><td></td><td>32</td><td>a+c</td><td></td><td></td><td>2</td><td>blank</td><td></td><td></td><td>abc: 3x16</td></tr><tr><td></td><td></td><td></td><td>16</td><td>a</td><td></td><td></td><td>blank</td><td></td><td></td><td></td><td>a+c: 2x16</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>a: 1x16</td></tr></table>			DIN41612 STYLE HALF C MALE RIGHT-ANGLE												ORDERING CODE								CONTACT DETAILS					Style	M=Male F=Female	No of pins	Rows loaded	Pin type	Plating Class	Board lock	Pin length in mm	Cross section	Pin load	Pin type/direction	A -	HC	M	xx	xx	x	-	x	x				Options (if another contact loading option is needed, please contact your sales office)												A -	HC	M	48	abc	R	-	1	MC1	R:	3.00 (±0.25)	0.60x0.60(±0.03)				32	a+c			2	blank			abc: 3x16				16	a			blank				a+c: 2x16												a: 1x16	E
DIN41612 STYLE HALF C MALE RIGHT-ANGLE																																																																																																																					
ORDERING CODE								CONTACT DETAILS																																																																																																													
	Style	M=Male F=Female	No of pins	Rows loaded	Pin type	Plating Class	Board lock	Pin length in mm	Cross section	Pin load	Pin type/direction																																																																																																										
A -	HC	M	xx	xx	x	-	x	x																																																																																																													
Options (if another contact loading option is needed, please contact your sales office)																																																																																																																					
A -	HC	M	48	abc	R	-	1	MC1	R:	3.00 (±0.25)	0.60x0.60(±0.03)																																																																																																										
			32	a+c			2	blank			abc: 3x16																																																																																																										
			16	a			blank				a+c: 2x16																																																																																																										
											a: 1x16																																																																																																										
F									F																																																																																																												
G	RoHS compliant Unit:mm		Scale	Free				Date	Name	Description: DIN 41612		G																																																																																																									
TOLERANCE						Drawn	30.08.2012	Amy	Type Half C / Male / R/A Board-lock																																																																																																												
X.			±X				Approved	17.08.2020	Winnie	ASSMANN WSW-No.																																																																																																											
X.X			±0.40							A-HCMxxxxx-xxx																																																																																																											
X.XX			±0.25	②	Change to new plant	17.08.2020	Winnie																																																																																																														
H			X.XXX	±0.15	①	Update dimension & plating	13.11.2019	Carson			Drawing-No.	ASS 4948 CO	rev02	H																																																																																																							
			①	Drawn	30.08.2012	Amy	Customer-No.	SHEET 4 / 4																																																																																																													
	DIM	TOL	①	Id.	Modification	Date	Name																																																																																																														
	Angle	±3°																																																																																																																			
	1	2	3	4	5	6	7	SV4824																																																																																																													