



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
- 1. BRASS PER QQ-B-626
  - 2. BERYLLIUM COPPER PER QQ-C-530
  - 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  - 4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
  - 5. TEFLON MIL-P-19468
  - 6. JIS H 3260, C 3501

- 1. CRIMPED FERRULE  
HEX CRIMP SIZE .18"
- 2. CONTACT PIN TO SOLDER

7	FERRULE	NOTE 6	NOTE 3	1	FR-53/46X127C
6	CONTACT PIN	NOTE 1	NOTE 4	1	1231121D2-6-08 /035
5	OUT CONTACT	NOTE 2	NOTE 4	1	1231121D1-6-B
4	INSULATOR	NOTE 5	NATURAL	1	1231121D2-4T -75
3	SPRING	NOTE 2	NATURAL	1	123-PLUG-SPR
2	BDDY	NOTE 1	NOTE 3	1	1231121D3-2- 36/22
1	SHELL	NOTE 1	NOTE 3	1	1231121D2-1
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS				PART NO. 1231121D3-N/3GT3G-16-75	
UNLESS OTHERWISE SPECIFIED TOLERANCES				APPROVED	DATE
0.5-6 = ±0.2					10-11-01'
6-30 = ±0.4				CHECKED	DATE
30-120 = ±0.6					10-11-01'
120-315 = ±1				DRAWN	DATE
315-1000 = ±1.6					10-11-01'
1000-2000 = ±2.4				FILE NO.	

<b>Amphenol</b>	
TITLE 1.0/2.3 CRIMP PLUG (FOR BT3002, 46431 CABLE)	
DRAWING NO. KJ-1231121D3-N/3GT3G-BT3002-75	
ITEM NO.	