Product data sheet Characteristics

XUB9ANANL5

photo-electric sensor - XUB - polarised - Sn 2m - 12..24VDC - cable 5m

Price*: 63.00 USD

XUB9ANANL5 has not been replaced. Please contact your customer care center for more information.



① Discontinued

Range of product	OsiSense XU	
Series name	General purpose single mode	
Electronic sensor type	Photo-electric sensor	
Sensor name	XUB	
Sensor design	Cylindrical M18	
Detection system	Polarised reflex	
Material	Plastic	
Line of sight type	Axial	
Type of output signal	Discrete	
Supply circuit type	DC	
Wiring technique	3-wire	
Discrete output type	NPN	
Discrete output function	1 NO	
Electrical connection	Cable	
Cable length	16.4 ft (5 m)	
Product specific application	-	
Emission	Red polarised reflex	
[Sn] nominal sensing distance	6.56 ft (2 m) polarised reflex need reflector XUZC50	

Complementary

		9
Enclosure material	PBT	
Lens material	PMMA	<u>.</u> 0
Maximum sensing distance	9.84 ft (3 m) polarised reflex	
Output type	Solid state	et a
Add on output	Without	
Wire insulation material	PvR	<u>.</u> 2
Status LED	1 LED (yellow) output state	
[Us] rated supply voltage	1224 V DC with reverse polarity protection	Ę
Supply voltage limits	1036 V DC	ةً -
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)	į
Switching frequency	<= 500 Hz	

Voltage drop	1.5 V (closed state)
Current consumption	35 mA (no-load)
Delay first up	< 15 ms
Delay response	< 1 ms
Delay recovery	< 1 ms
Setting-up	Without sensitivity adjustment
Diameter	0.71 in (18 mm)
Length	2.44 in (62 mm)

Environment

Product certifications	CE CSA UL	
Ambient air temperature for operation	-13131 °F (-2555 °C)	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Vibration resistance	7 gn, amplitude = +/- 1.5 mm (f = 1055 Hz) conforming to IEC 60068-2-6	
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60068-2-27	
P degree of protection IP65 double insulation conforming to IEC 60529 IP67 double insulation conforming to IEC 60529		

Ordering and shipping details

Category	22415 - SENSORS, PHOTOELECTRIC, BASIC
Discount Schedule	DS2
GTIN	003389110395945
Nbr. of units in pkg.	1
Package weight(Lbs)	0.410000000000003
Returnability	N
Country of origin	ID

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity

Contractual warranty

Warranty period	18 months