



SD

3155-2-5

- NOTES:
1. FOR USE WITH ANDREWS FSJ4-50B AND FSJ4RN-50B CABLE (1/2 IN HELIAX).
 2. INTERFACE PER, IEC STANDARD 169-4 (TYPE 7-16 MM).
 3. FOR CABLE INSTRUCTIONS SEE: 3-654-1.
 - 3A. FOR CABLE OUTER CONDUCTOR FLARING USE KTH-9000.
 4. MATERIALS:
O RINGS & GASKET: SILICONE RUBBER.
INSULATOR: TEFLON.
ALL METAL PARTS: BRASS.
 5. FINISHES:
CENTER CONTACT: SILVER PLATE.
ALL METAL PARTS: KINGS TARNISH RESISTANT WHITE BRONZE ALLOY (TR-3) OR SILVER PLATE.
FOR SILVER PLATE, ORDER PART NUMBER AS SHOWN. FOR WHITE BRONZE PLATING, ADD "MJ3" SUFFIX TO THE PART NUMBER SHOWN, FOR EXAMPLE 3155-2-5 MJ3.
 6. ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE: 50 OHMS.
FREQUENCY RANGE: DC TO 6.0 GHz.
OPERATING VOLTAGE: 2700 VRMS.

STAMP: KINGS 3155-2-5
YRWK (DATE CODE)
(SEE NOTE 5)

1.25 HEX REF.

SD

REVISIONS	
ISSUE	CHANGES
0	ER 38187 HVN 01/18/01
1	CN 38377 A HVN 08/14/01
2	CN 38442 E TML 11/29/01

3155-2-5S	
SCALE 3:1	
APPROX SURFACE AREA	
WAS: E-19248C	
USED ON	
REF:	
7-16, PL, STRAIGHT	
DRAWN HVN	DATE 03/01/01
DESIGN LJ	DATE 10/10/97
APPR.	DATE
 KINGS ELECTRONICS CO., INC. ROCK HILL, SOUTH CAROLINA 29730	
3155-2-5	