


# Spade and Ring Series

## Pre-Insulated

**.250 Snap Spade**  
**.032 Electro-Tinned Phosphor Bronze**  
**22-18 AWG (Red)**


S P A D E & R I N G

STYLE AND DIMENSIONS	STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	
		.117	.147	.180						
	6	X			B	✓	*	5000	50780	
			X			B	✓	*	4000	50780-8
				X		B	✓	*	4000	50780-8A
		X				W	✓	*	5000	50781
			X			W	✓	*	4000	50781-8
				X		W	✓	*	4000	50781-8A

# Spade and Ring Series

## Pre-Insulated


**.280 Snap Spade**  
**.032 Electro-Tinned Phosphor Bronze**  
**22-18 AWG (Red)**

STYLE AND DIMENSIONS	STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	
		.117	.147	.180						
	8	X			B	✓	*	5000	50786	
			X			B	✓	*	4000	50786-8
				X		B	✓	*	4000	50786-8A
		X				W	✓	*	5000	50787
			X			W	✓	*	4000	50787-8
				X		W	✓	*	4000	50787-8A

# Spade and Ring Series

## Pre-Insulated

**.330 Snap Spade**  
**.032 Electro-Tinned Phosphor Bronze**  
**22-18 AWG (Red)**

STYLE AND DIMENSIONS	STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	
		.117	.147	.180						
	10	X			B	✓	*	5000	50792	
			X			B	✓	*	4000	50792-8
				X		B	✓	*	4000	50792-8A
		X				W	✓	*	5000	50793
			X			W	✓	*	4000	50793-8
				X		W	✓	*	4000	50793-8A

Recommended Strip Length  $\frac{3}{32} \pm \frac{1}{32}$   
 \* Contact Factory for Latest Agency Approvals.