



AE101SD1CB Product Details

[Share](#) [Print](#) [Email](#)



AE101SD1CB
(2-1437556-7)

TE Internal Number: 2-1437556-7

Superseded

[Search for Replacement Parts](#)

Toggle Switches

Not EU RoHS or ELV Compliant (Find RoHS Compliant Alternates)

Product Highlights:

- AE Series
- Single Pole - Double Throw Configuration (Pole-Throw)
- Current Rating = 0.4 VA A
- Mount Style = Through-Hole
- Termination Type = Printed Circuit, Vertical

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Dimensional Drawing](#)

Related Products:

- [Tooling](#)

Feedback

Product Features (Please use the Product Drawing for all design activity)

Electrical Characteristics:

- Current Rating (A) = 0.4 VA

Termination Features:

- Termination Type = Printed Circuit, Vertical
- Seal Type = Terminal Seal (epoxy)

Dimensions:

- Toggle Length (mm [in]) = 7.15 [0.282]

Body Features:

- Mount Style = Through-Hole
- Bushing Style = Unthreaded
- Bushing Type = Plain

Contact Features:

- Contact Plating = Gold

Housing Features:

- Toggle Style = Baton Long
- Process Sealed = Yes

Configuration Features:

- Configuration (Pole-Throw) = Single Pole - Double Throw
- Operating Function = On None On

Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C
- UL Flammability Rating = UL 94V-0

Other:

- Series = AE
- Brand = Alcoswitch
- Comment = Process seal meets MIL-STD-202, Method 112 test cond. A & D at 85°C.

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed



