



NOTES:

1. FOR USE WITH BOEING BMS13-65 OJ & ADAMS RUSSELL FC38Z CABLES.
2. FOR CABLING INSTRUCTIONS SEE 3-546-2.
3. FOR CRIMPING USE DIE KTH-2213.
4. INTERFACE PER MIL-STD-348, FIG. 302-1.
5. CENTER CONTACT (1-856-15MA9) SUPPLIED UNASSEMBLED.
6. MARK PACKAGE: KINGS 795-29-9 (DATE CODE)
7. MATERIALS:
 INSULATOR: TEFLON, ASTM D1710
 GASKET: SIL. RUB., A-A-59588
 K-GRIP SLEEVE: COM. BRONZE ALLOY ASTM B135
 OUTER CONTACT, SPRING WASHERS: BER. COP., ASTM B196
 ALL OTHER PARTS: BRASS, ASTM B16
8. FINISHES:
 CENTER CONTACT: .000050 MIN GOLD PLATE PER ASTM B488 OVER .000050 MIN NICKEL PER AMS-QQ-N-290 (RoHS)
 OUTER CONTACT, SPRING WASHERS: .000200 MIN SILVER PER ASTM B700 OVER .000020 MIN COPPER PER ASTM B734 (RoHS)
 ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
9. ELECTRICAL CHARACTERISTICS:
 NOMINAL IMPEDANCE: 50 OHMS
 VOLTAGE RATING: 1000 VRMS
 FREQUENCY RANGE: DC TO 11 GHz
 INSERTION LOSS: DC TO 1.9 GHz, 0.025 dB MAX
 1.9 TO 5.0 GHz, 0.065 dB MAX
10. WEIGHT: 28.2 GRAMS

795-29-9

REVISIONS

ISSUE	CHANGES
B	ER 8354 RMS 05/28/08
C	REVISED PER DMF304 & ER35388 TZ 11/08/11

CUSTOMER SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1

APPROX SURFACE AREA

CAGE CODE: 91836

REF: BOEING

PLUG, C

DRAWN	VLS	DATE	05/03/95
DESIGN	VLS	DATE	05/03/95
APPR.	VLS	DATE	05/03/95

KINGS
by WINCHESTER ELECTRONICS

Winchester Electronics
62 Barnes Industrial
Road North
Wallingford, CT 06492

795-29-9