



Frequency (MHz)

P_{1dB} Compression Point




Frequency (MHz)

Reverse Isolation




Frequency (MHz)

Input VSWR



Frequency (MHz)

Output VSWR



Frequency (MHz)

S-Parameters

Frequency	S11 Mag	S11 Ang	S21 Mag	S21 Ang	S12 Mag	S12 Ang	S22 Mag	S22 Ang
1700.0	0.270	33.00	3.810	37.00	0.200	-19.00	0.160	-11.00
1800.0	0.220	29.00	3.860	25.00	0.200	-21.00	0.120	-39.00
1900.0	0.170	29.00	3.900	13.00	0.200	-23.00	0.100	-80.00
2000.0	0.130	43.00	3.930	1.00	0.190	-22.00	0.100	-130.00
2100.0	0.130	67.00	3.840	-13.00	0.200	-21.00	0.130	-167.00
2200.0	0.160	83.00	3.690	-26.00	0.210	-22.00	0.170	164.00
2300.0	0.230	86.00	3.430	-39.00	0.210	-23.00	0.210	140.00

Absolute Maximum Conditions

Maximum Operating Temperature	-55.0 - 100.0 °C	Maximum Storage Temperature	-62.0 - 125.0 °C
Maximum Case Temperature	125.0 °C	Maximum Supply Voltage	18.0 Volts
Continuous RF Input Power	13.0 dBm	Short Term RF Input Power (1 minute max)	50.0 mW
Maximum Peak Power (3 µsec max)	0.5 W		

Amplifonix | 2707 Black Lake Place | Philadelphia, PA 19154
Tel: 215.464.4000 | FAX: 215.464.4001 | Email: info@amplifonix.com

i2 Technologies US, Inc.

HTML Pages converted to PDF Document

This document contain component information from the manufacturer's website which are not available in a revision controlled document from the manufacturer. To facilitate the addition of these parts into the Electronics Database, we are converting the HTML pages related to that part, from the manufacturer's website into Adobe PDF format. The contents of this document is based on the information provided on the manufacturer's website, therefore the information may have been changed by the manufacturer since this was created.

