

CAT. N° 4 199 15



## MCB RX³ 6000 - 4P 400 V~ - 10 A - C CURVE - PRONG-TYPE SUPPLY BUSBARS

|                        |          |
|------------------------|----------|
| Pack (number of units) | 3        |
| Volume (dm³)           | 1,864    |
| Weight (g)             | 1 565,00 |

### Product characteristics

#### 4-pole 400 V~

- C curve
- Nominal rating In : 10 A
- Number of modules : 4

### General characteristics

#### MCBs RX³ 6000 - thermal magnetic MCBs from 6 A to 63 A - C curve

- Conform to IEC 60898-1
- Do not accept auxiliaries, and add-on modules
- Compatible with prong-type supply busbars
- Breaking capacity:
  - 6000 - IEC 60898-1 - 230/400 V~
  - 6 kA - IEC 60947-2 - 230/400 V~
  - 10000 - IEC 60898-1 - 127/220 V~
  - 10 kA - IEC 60947-2 - 127/220 V~

### Documentation



#### Catalogue pages & additional information

- [Description page \(p.052\)](#)
- [Dimensions of din-rail equipment](#)



#### Agreements & certificates of conformity

- [OC / CB-IT-21483/A1](#)
- [VDE-40042228](#)



#### Installation & technical data

- [F01910EN-01](#)



#### Environmental product profile

- [LGRP-00698-V01](#)