



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. SILVER PL. 120 MIN. THICK OVER COPPER STRIKE
 3. BERYLLIUM COPPER PER QQ-C-530
 4. SILVER PL. 200 MIN. THICK OVER COPPER STRIKE
 5. TEFLON MIL-P-19468
 6. BLUE, PER PANTONE 3005C
 7. JIS H 3250, C 2700

1. CRIMPED FERRULE
 HEX CRIMP SIZE .429"

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
10	NUT			1	7166451A2-6
9	FERRULE			1	FR-124/109X158
8	COVER	PE		1	7166141A1-9
7	GASKET	N. B. R.	BLACK	1	GS-415/355XD30
6	PIN			1	7166451A2-5
5	BARREL			1	7161111A2-1-93/74
4	GASKET	SILICONE	RED	1	GS-215/183XD16
3	CONTACT PIN			1	7166411A1-3-39/29
2	INSULATOR		NATURAL	1	7161111A1-2T-L400
1	BODY			1	7166411A1-1

DIMENSIONS ARE IN MILLIMETERS			PART NO.	
UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4			7166411A1-120STS-7C-50	
			APPROVED	DATE
			10-11-01'	
			CHECKED	DATE
10-11-01'				
DRAWN	DATE			
10-11-01'				
SCALE	1.5/1	ISSUE	A	
FILE NO				

Amphenol		TITLE	7/16 BULKHEAD CRIMP JACK (FOR BELDEN 9913, 9914, LMR400)
		DRAWING NO.	KJ-7166411A1-120STS-9913-50
		ITEM NO.	