

# In-Line Optical Attenuators, Flat Wavelength, FC UPC

FC UPC, 12 dB

CORNING

Corning offers in-line, flat wavelength optical attenuators that are easily inserted between the connector and adapter in an “in-line” configuration and are compatible with SC, ST<sup>®</sup> compatible, FC, MU, LC and angled SC and FC connectors. A fundamental element of these Corning attenuators is the zirconia ferrule containing a specially selected attenuating fibre. This special fibre minimizes the effect of modal interference and gives the component a flat spectral response. It is extremely stable over the wavelength range of 1260 to 1360 nm and 1430 to 1580 nm. These in-line, flat wavelength attenuators are available in ultra PC ( $\leq$  -55 dB) and angled PC ( $\leq$  -65 dB) finish to meet the most demanding network reflectance requirements.

## Features and Benefits

### Fully compatible with FC fibre optic connectors

No intermateability concerns

### Numerical identification mark on housing

Easy indication of attenuation levels

### Attenuator incorporated inside standard FC adapter housings

Compatible with standard distribution panels

## Standards

**Design And Test Criteria** Telcordia GR-910 issue 2 performance requirements



Part Number: ATN-54-12



Part Number: ATN-54-12

# In-Line Optical Attenuators, Flat Wavelength, FC UPC

FC UPC, 12 dB

CORNING

## Specifications

### General Specifications

Attenuator type	In-Line
Compatibility	FC
Packaging	Single Pack
Product type	Attenuators

### Temperature Range

Operation	-25 °C to 70 °C (-13 °F to 158 °F)
-----------	------------------------------------

### Design - Connector

Ferrule Material	Zirconia
Housing material	Metal
Housing Colour	Metal

### Optical Specifications - Connector

Attenuation	12 dB
Attenuation Tolerance	± 1.2 dB
Insertion Loss	1.2 dB

### Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

## Ordering Information

Part Number	ATN-54-12
Product Description	FC UPC In-Line Optical Attenuator, Flat Wavelength
EAN Code	4042673807162

# In-Line Optical Attenuators, Flat Wavelength, FC UPC

FC UPC, 12 dB

The CORNING logo is displayed in white, uppercase letters within a solid blue square.

## Shipping Information

Units Per Delivery	1/1
Package Contents	Attenuator, FC UPC



**Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY  
00 800 2676 4641 · FAX: +49 30 5303 2335 · [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)**

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/emea/trademarks](http://www.corning.com/opcomm/emea/trademarks). Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2016 Corning Optical Communications. All rights reserved.