



備註 /NOTE:

1.安規 /SAFETY:

- 1-1. 規格 /RATING: 100V AC MAX or 12V DC 2A MAX
- 1-2. 絕緣阻抗 /INSULATION RESISTANCE: 50M ohm MIN at 250V DC
- 1-3. 絕緣耐壓 /WITHSTANDING: 250V AC at 1 MINUTE

2.材質 /MATERIAL:

- 2-1. 外套 /PLASTIC COVER:ABS
- 2-2. 銅管 /SHELL: 黃銅 /BRASS
- 2-3. 上蓋 /CAP: 黃銅 /BRASS
- 2-4. 線扣 /CABLE FIXER: 黃銅 /BRASS
- 2-5. 膠芯 /HOUSING: PBT
- 2-6. 針 /PIN: 黃銅 /BRASS
- 2-7. 塑膠雙腳 /POM RING: POM
- 2-8. 彈簧 /SPRING: 鋼 /STEEL
- 2-9. 中筒 /PLASIC TUBE: ABS
- 2-10. SR: PVC

3. 電鍍 /PLATING:

- 3-1. 銅管 /SHELL: 鍍 /NICKEL
- 3-2. 上蓋 /CAP: 鍍 /NICKEL
- 3-3. 線扣 /CABLE FIXER: 錫 /TIN
- 3-4. 針 /PIN: 銀 /SILVER



ORETHANALL
CONNECTORS
ASSEMBLIES

煜倫有限公司

PART NO. MDP-PA-04		CHECKED BY CY		TOLERANCES ARE		DESCRIPTION: POWER 4P 公座 成品 系列	
DWG NO. MDP-PA-04		DRAWING BY		X ±0.1		AREA	
FILE NO. NY-DW286		PROJECTION		XX ±0.05		REVISIONS	
UNIT / mm		SCALE 1:1		AWG		HK	
						DATE	