

LC Connectors

LC Type Fiber Optic Connectors

FEATURES

- Intermateable with Lucent Technologies LC connectors
- Satisfies flame resistance standard UL94V-0 (excluding cap)
- Zirconia ceramics ferrule and sleeve for high-performance and high reliability

PERFORMANCE

	Singlemode	
	Insertion Loss	Return Loss
UPC Polishing	0.5 dB or less	50 dB or more

Condition: against master plug

Housing SLC-P1 Series



Designed for \varnothing 0.9 mm Cable Singlemode

- Plastic stop ring for simultaneous ease of assembly
- Combined with LCZ-1A ferrule provides high performance

ORDERING INFORMATION

Singlemode

Model Number	Type Number									
SLC-P1	3	1	1	2	5	0	3	3	0	0

Boot Color	3	White
Boot I.D. (mm)	1	0.9 (plastic)
Ferrule I.D. (μ m)	\varnothing 125 \varnothing 126	

Package	3	Bulk
Cap	3	White frame
Marking of Boot	1	SII

(Required)

Housing SLC-P2 Series



Simplex Designed for \varnothing 2.0 mm Cable Singlemode

- Use of heat-shrink tube with adhesive for compatibility with \varnothing 1.6- \varnothing 2 mm cables
- Combined with LCZ-1A ferrule provides high performance

ORDERING INFORMATION

Singlemode

Model Number	Type Number									
SLC-P2	3	2	1	2	5	0	3	3	0	0

Boot Color	3	Light Grey
Boot I.D. (mm)	1	1.6~2.0 (plastic)
Ferrule I.D. (μ m)	\varnothing 125 \varnothing 126	

Package	3	Bulk
Cap	3	White frame
Marking of Boot	1	SII

(Required)