


SRI2.5-PNP=LED(RD)220VAC

- 36 Connections



Phoenix Mecano Brand

Technical Data


Wire sizes		Insulating Material	
Solid min	0.2 mm ²	Material	PA 6.6
Solid max	4.0 mm ²	Flammability Class	UL 94 V-2
Stranded (flexible) min	0.2mm ²	Temperatures	
Stranded (flexible) max	4.0 mm ²	Working Temperature	-40 - 105 °C
Stranded with Ferrule min	0.2 mm ²	Dimensions	
Stranded with Ferrule max	2.5 mm ²	Stripped Length	7.0 mm
Clamping Range min	0.2mm ²	Width	5.0 mm
Clamping Range max	4.0 mm ²	Length	62.8 mm
		Height TS35 x 7.5	58.3 mm
		Height TS32	62.8 mm

Electrical Data

General

Electronic Components

Rated Voltage AC 220 V

Colours
 BEIGE, similar RAL 1019
Connection Diagram

Bitte kontaktieren Sie unsere Vertriebsmitarbeiter.
Please contact our sales department.

Order Data

Article Designation	Article Number	PU
SRI2.5-PNP=LED(RD)220VAC-BE	41275.2	100

Accessoires

Article Designation	Article Number	PU
End Plate AP2.5/I	492698.2	20
Quick Labelling PSB5/50	494600.7	500