

COAXIAL ATTENUATORS

SMA

50 WATTS MEDIUM POWER

Part Number	Frequency range (GHz)	ATTENUATION (dB)				V.S.W.R.			Power (W)		Weight (Max) (g)
		Nominal	DEVIATION			DC - 1	1 - 2	2 - 3	avg.	peak	
			DC - 1	1 - 2	2 - 3						
R417103139	DC - 1	3	± 0.5			≤ 1.10			50	5000	280
R417106139		6	± 0.5			≤ 1.10			50	5000	280
R417110139		10	± 0.5			≤ 1.10			50	5000	280
R417120139		20	± 0.7			≤ 1.10			50	5000	280
R417130139		30	± 0.7			≤ 1.10			50	5000	280
R417103138	DC - 2	3	± 0.6			≤ 1.10	≤ 1.25		50	5000	280
R417106138		6	± 0.6			≤ 1.10	≤ 1.25		50	5000	280
R417110138		10	± 0.6			≤ 1.10	≤ 1.25		50	5000	280
R417120138		20	± 1.0			≤ 1.10	≤ 1.25		50	5000	280
R417130138		30	± 1.0			≤ 1.10	≤ 1.25		50	5000	280
R417103130	DC - 3	3	± 0.7			≤ 1.10	≤ 1.25	≤ 1.35	50	5000	280
R417106130		6	± 0.7			≤ 1.10	≤ 1.25	≤ 1.35	50	5000	280
R417110130		10	± 0.7			≤ 1.10	≤ 1.25	≤ 1.35	50	5000	280
R417120130		20	± 2.0			≤ 1.10	≤ 1.25	≤ 1.35	50	5000	280
R417130130		30	± 2.0			≤ 1.10	≤ 1.25	≤ 1.35	50	5000	280

NOTA : These attenuators must be used with conduction cooling, a 78 sq. in. plate *1/8" (500 cm²* 3mm) min. is required.

