

NOTICE OF REVISION (NOR)

(See MIL-STD-480 for instructions)

DATE (YYMMDD)

93-04-07

Form Approved
OMB No. 0704-0188

This revision described below has been authorized for the document listed.

Public reporting burden for this collection is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Information and Regulatory Affairs, Office of Management and Budget, Washington, DC 20503.

1. ORIGINATOR NAME AND ADDRESS

Defense Electronics Supply Center
Dayton, Ohio 45444-5277

2. CAGE CODE

67268

3. NOR NO.

5962-R054-93

4. CAGE CODE

67268

5. DOCUMENT NO.**86008****6. TITLE OF DOCUMENT**

MICROCIRCUITS, LINEAR, HIGH-SPEED VOLTAGE COMPARATOR, MONOLITHIC SILICON

7. REVISION LETTER

(Current) B

(New) C

8. ECP NO.

86008ECP-1

9. CONFIGURATION ITEM (OR SYSTEM) TO WHICH ECP APPLIES**10. DESCRIPTION OF REVISION**

Sheet 1: Revisions ltr column; add "C"
Revisions description column; add "Changes in accordance with NOR 5962-R054-93".
Revisions date column; add "93-04-07".
Revision level block; add "C".
Revision status of sheets; For sheets 1, 7, 8, 9, 11, and 12, add "C".

Sheet 7: TABLE I.
Propagation delay time test, device type 01, group A subgroups 9 and 11, min limit column, delete 4.5 ns and substitute 3.5 ns.
Propagation delay time and latch enable to output test, add footnote 5/.
Revision level block; add "C".

Sheet 8: TABLE I. Footnote 7/.
Delete sentence "b" and substitute the following; "b. t_{PD+} on either output \bar{Q} or \bar{Q} is performed."
Delete sentence "c" and substitute the following; "c. t_{PD-} on either output \bar{Q} or \bar{Q} is performed."
Revision level block; add "C".

Sheet 9: FIGURE 1. Terminal connections. For case outline I, pin 6, delete "NC" and substitute "NC/HYSTERESIS".
For case outline E, pin 9, delete "NC" and substitute "NC/HYSTERESIS".
Revision level block; add "C".

CONTINUED ON NEXT SHEET

11. THIS SECTION FOR GOVERNMENT USE ONLY**a. CHECK ONE**

EXISTING DOCUMENT SUPPLEMENTED BY THIS NOR MAY BE USED IN MANUFACTURE.

REVISED DOCUMENT MUST BE RECEIVED BEFORE MANUFACTURER MAY INCORPORATE THIS CHANGE.

CUSTODIAN OF MASTER DOCUMENT SHALL MAKE ABOVE REVISION AND FURNISH REVISED DOCUMENT TO:

b. ACTIVITY AUTHORIZED TO APPROVE CHANGE FOR GOVERNMENT

DESC-ECS

SIGNATURE AND TITLE

MICHAEL A. FRYE
BRANCH CHIEF

DATE (YYMMDD)

93-04-07

12. ACTIVITY ACCOMPLISHING REVISION

DESC-ECS

REVISION COMPLETED (Signature)

RICK C. OFFICER

DATE (YYMMDD)

93-04-07

10. DESCRIPTION OF REVISION - CONTINUED

Document No.:	86008
Revision:	C
NOR No.:	5962-R054-93
Sheet:	2 of 2

- Sheet 11: TABLE II. Delete the second sentence at the bottom of table and substitute the following;
"*** Subgroups 9, 10, and 11, if not tested, shall be guaranteed to the limits in table I herein."
Revision level block; add "C".
- Sheet 12: 6.4. Approved sources of supply. Under military drawing part numbers 8600803EX and 8600803IX,
delete vendor CAGE number 34335 and substitute footnote "2". Footnote 2/ states, "Not available
from an approved source of supply".

1.3 Absolute maximum ratings.

Positive supply voltage (V+):	
Device types 01, 02, 03 - - - - -	+7 V dc
Device type 04 - - - - -	+6.5 V dc
Negative supply voltage (V-):	
Device types 01, 02, 03 - - - - -	-7 V dc
Device type 04 - - - - -	-6.5 V dc
Input voltage range (V _I):	
Device types 01, 02, 03 - - - - -	+4 V dc
Device type 04 - - - - -	+5 V dc
Differential input voltage (V _{ID}):	
Device types 01, 02, 03 - - - - -	+6 V dc
Device type 04 - - - - -	+5.5 V dc
Storage temperature range - - - - -	-65°C to +150°C
Maximum power dissipation (P _D):	
Device types 01, 02 - - - - -	500 mW
Device types 03, 04 - - - - -	300 mW
Lead temperature (soldering, 10 seconds) - - - - -	+300°C
Thermal resistance, junction-to-case (θ _{JC}):	
Cases E, I, 2 - - - - -	See MIL-M-38510, appendix C
Junction temperature (T _J) - - - - -	+175°C
Thermal resistance, junction-to-ambient (θ _{JA}):	
Case E - - - - -	120°C/W
Case I - - - - -	140°C/W
Case 2 - - - - -	92.3°C/W
Output current - - - - -	30 mA

1.4 Recommended operating conditions.

Positive supply voltage (V+):	
Device types 01, 02, 03 - - - - -	+6.0 V dc
Device type 04 - - - - -	+5.0 V dc 1/
Negative supply voltage (V-):	
Device types 01, 02, 03 - - - - -	-5.2 V dc
Device type 04 - - - - -	-5.2 V dc 1/
Ambient operating temperature range (T _A) - - - - -	-55°C to +125°C 2/
Minimum operating voltage (V+ to V-) - - - - -	9.7 V dc
Latch enable voltage:	
V _{IH} - - - - -	-.85 V
V _{IL} - - - - -	-1.65 V

1/ $\sqrt{V_{IN}}$ < positive supply and negative supply voltage.

2/ Devices require a thermal equilibrium to be established with a transverse airflow of >500 LFPM.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	86008
	REVISION LEVEL B	SHEET 3

2. APPLICABLE DOCUMENTS

2.1 Government specification and standard. Unless otherwise specified, the following specification and standard, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

STANDARD

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

(Copies of the specification and standard required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.2 Case outlines. The case outlines shall be in accordance with 1.2.2 herein.

3.3 Electrical performance characteristics. Unless otherwise specified, the electrical performance characteristics are as specified in table I and apply over the full ambient operating temperature range.

3.4 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the part number listed in 1.2 herein. In addition, the manufacturer's part number may also be marked as listed in 6.4 herein.

3.5 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in 6.4. The certificate of compliance submitted to DESC-ECS prior to listing as an approved source of supply shall state that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

3.6 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

3.7 Notification of change. Notification of change to DESC-ECS shall be required in accordance with MIL-STD-883 (see 3.1 herein).

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		86008
		REVISION LEVEL B	SHEET 4

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions -55°C ≤ T _A ≤ +125°C unless otherwise specified 1/ 2/ 3/ 4/	Device types	Group A subgroups	Limits		Unit
					Min	Max	
Input offset voltage	V _{IO}	R _S = 100Ω, V _{CM} = 0 V dc	A11	1	±2.0		mV
				2, 3	±3.0		
Input offset voltage temperature coefficient 5/	ΔV _{IO} ΔT	R _S = 100Ω V _{CM} = 0 V	01, 02	1, 2, 3	±10		μV/°C
			03		±15.0		
			04		±20		
Input offset current	I _{IO}	V _{CM} = 3.3 V T _A = +25°C	01, 02	1	±1.0		μA
			03		±1.5		
		V _{CM} = +.5 V T _A = +25°C	04	±1.0			
			-V _{CM} = -3.3 V T _A = +125°C, -55°C	01, 02	2, 3	±1.6	
		03		±3.0			
		-V _{CM} = -.5 V T _A = +125°C, -55°C	04	±1.6			
Input bias current	I _{IB}	V _{CM} = 3.3 V T _A = +25°C	01, 02	1	10		μA
			03		15		
		V _{CM} = +.5 V T _A = +25°C	04	10			
			-V _{CM} = -3.3 V T _A = +125°C, -55°C	01, 02	2, 3	16	
		03		30			
		-V _{CM} = -.5 V T _A = +125°C, -55°C	04	16			

See footnotes at end of table.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	86008
	REVISION LEVEL B	SHEET 5

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions -55°C ≤ T _A ≤ +125°C unless otherwise specified 1/ 2/ 3/ 4/	Device types	Group A subgroups	Limits		Unit
					Min	Max	
Input voltage range	V _{CM}		01,02,03	1, 2, 3	-3.3	3.3	V
			04		-2.5	+5.0	
Input voltage common mode rejection ratio	CMRR	R _S = 100Ω, -3.3 V ≤ V _{CM} ≤ +3.3 V	01,02,03	4, 5, 6	80		dB
		-2.5 ≤ V _{CM} ≤ +5.0 V	04				
Power supply rejection ratio	PSRR	R _S = 100Ω, ΔV _S = ±5%	A11	4, 5, 6	60		dB
High level output voltage	V _{OH}	T _A = +25°C	01,02,03	1	-0.960	-0.810	V
		T _A = +125°C		2	-0.850	-0.620	
		T _A = -55°C		3	-1.10	-0.920	
				04	1, 2, 3	-1.10	
Low level output voltage	V _{OL}	T _A = +25°C	01,02,03	1	-1.85	-1.65	V
		T _A = +125°C		2	-1.81	-1.57	
		T _A = -55°C		3	-1.91	-1.69	
				04	1, 2, 3		

See footnotes at end of table.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	86008
	REVISION LEVEL B	SHEET 6

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions -55°C < T _A < +125°C unless otherwise specified <u>1/ 2/ 3/ 4/</u>	Device types	Group A subgroups	Limits		Unit
					Min	Max	
Positive supply current	I+		01,02,03	1, 2, 3		22	mA
			04			9	
Negative supply current	I-		01, 02	1, 2, 3		-26	mA
			03, 04			-18	
Propagation delay time	t _{pd} [±]	T _A = -55°C, +25°C <u>6/ 7/</u>	01	9, 11	4.5	6.5	ns
		T _A = +125°C <u>6/ 7/</u>			10	5.5	
		T _A = +25°C, -55°C <u>6/ 7/</u>	02	9, 11	0.5	6.5	
		T _A = +125°C <u>6/ 7/</u>			10	0.5	
		T _A = +25°C, -55°C <u>7/ 8/</u>	03	9, 11	2.0	4.0	
		T _A = +125°C <u>7/ 8/</u>			10	1.5	
		T _A = +25°C, -55°C <u>9/</u>	04	9, 11	1.5	3.5	
		T _A = +125°C <u>9/</u>			10	1.5	
Propagation delay time Latch enable to output	t _{pd} [±] (E)	T _A = +25°C, -55°C	01, 03	9, 11		8	ns
		T _A = +125°C			10		
		T _A = +25°C, -55°C	02	9, 11		8	
		T _A = +125°C			10		
		T _A = +25°C,	04	9		3.5	
		T _A = +125°C, -55°C			10, 11		

See footnotes on top of next page.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		86008
		REVISION LEVEL B	SHEET 7

- 1/ For device types 01, 02, and 03 unless otherwise specified: $V^+ = +6.0$ V dc; $V^- = -5.2$ V dc; $V_T = -2.0$ V dc, and $R_L = 50\Omega$.
- 2/ Devices require a thermal equilibrium to be established with a transverse airflow of >500 LFPM.
- 3/ Production pulse test devices at correlated temperatures of -35°C and $+145^\circ\text{C}$ to compensate for high power steady-state operation.
- 4/ For device type 04 unless otherwise specified: $V^+ = +5.0$ V dc; $V^- = -5.2$ V dc; $V_T = -2.0$ V dc, and $R_L = 50\Omega$.
- 5/ Guaranteed if not tested to the limits specified.
- 6/ 100 mV step input with 5 mV overdrive.
- 7/
 - a. This parameter tested with $V_{CM} = 0$ V and supplies $V^+ = 6.0$ V, $V^- = -5.2$ V.
 - b. Only t_{pd}^+ on output Q .
 - c. Only t_{pd}^- on output \bar{Q} .
- 8/ 100 mV step input with 10 mV overdrive $V^+ = +5.0$ V; $V^- = -5.2$ V for 03.
- 9/ This parameter measured with 100 mV pulse (10 mV overdrive), to 50 percent of the transition output point.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	86008
	REVISION LEVEL B	SHEET 8

Device types	01, 02, 03, and 04		04
Case outlines	I	E	2
Terminal number	Terminal symbol		
1	V+	GROUND 1	NC
2	NONINVERTING INPUT	V+	GROUND 1
3	INVERTING INPUT	NONINVERTING INPUT	V+
4	LATCH ENABLE	INVERTING INPUT	NONINVERTING INPUT
5	V-	NC	INVERTING INPUT
6	NC	LATCH ENABLE	NC
7	Q OUTPUT	NC	NC
8	\bar{Q} OUTPUT	V-	LATCH ENABLE
9	GROUND 2	NC	NC
10	GROUND 1	NC	V-
11		Q OUTPUT	NC
12		\bar{Q} OUTPUT	NC
13		NC	NC
14		NC	Q OUTPUT
15		NC	\bar{Q} OUTPUT
16		GROUND 2	NC
17			NC
18			NC
19			NC
20			GROUND 2

NC = no connection

FIGURE 1. Terminal connections.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		86008
		REVISION LEVEL B	SHEET 9

3.8 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

a. Burn-in test, method 1015 of MIL-STD-883 .

(1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).

(2) $T_A = +125^{\circ}\text{C}$, minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

a. Tests shall be as specified in table II herein.

b. Subgroups 7 and 8 in table I, method 5005 of MIL-STD-883 shall be omitted.

4.3.2 Groups C and D inspections.

a. End-point electrical parameters shall be as specified in table II herein.

b. Steady-state life test conditions, method 1005 of MIL-STD-883.

(1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).

(2) $T_A = +125^{\circ}\text{C}$, minimum.

(3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		86008
		REVISION LEVEL B	SHEET 10

TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (per method 5005, table I)
Interim electrical parameters (method 5004)	---
Final electrical test parameters (method 5004)	1*, 2, 3, 4
Group A test requirements (method 5005)	1, 2, 3, 4, 5, 6, 9, 10, 11**
Groups C and D end-point electrical parameters (method 5005)	1

* PDA applies to subgroup 1.

** Subgroups 10 and 11, if not tested, shall be guaranteed to the specified limits in table I.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for OEM application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Comments. Comments on this drawing should be directed to DESC-ECS, Dayton, Ohio 45444, or telephone 513-296-5375.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		86008
		REVISION LEVEL B	SHEET 11

6.4 Approved sources of supply. Approved sources of supply are listed herein. Additional sources will be added as they become available. The vendors listed herein have agreed to this drawing and a certificate of compliance (see 3.5 herein) has been submitted to DESC-ECS.

Military drawing part number	Vendor CAGE number	Vendor similar part number <u>1/</u>
8600801EX	34335 64155	AM685/BEA LT685J/883
8600801IX	34335 64155	AM685/BIC LT685H/883
8600802EX	64155	LT685J/883
8600802IX	64155	LT685H/883
8600803EX	34335	AM6685/BEA
8600803IX	34335	AM6685/BIC
8600804EX	34031	AD96685TQ/883B
8600804IX	34031	AD96685TH/883B
86008042X	34031	AD96685TE/883B

1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		86008
		REVISION LEVEL B	SHEET 12

Vendor CAGE
number

Vendor name
and address

34031

Analog Devices, Incorporated
Computer Labs Division
7910 Triad Center Drive
Greensboro, NC 27409

34335

Advanced Micro Devices, Incorporated
901 Thompson Place
P.O. Box 3453
Sunnyvale, CA 94088

64155

Linear Technology Corp.
1630 McCarthy Blvd.
Milpitas, CA 95035-7487

**STANDARDIZED
MILITARY DRAWING**

DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

86008

REVISION LEVEL
B

SHEET
13