



552466-2

**PICABOND® Connector, 250 loose piece, 48 Vdc, pink**

- Lightweight, compact, and economical means of splicing multiconductor telephone cable
- No prestripping or cutting required, can tap without service interruptions, eliminates “turndowns”
- Color-coded to indicate size and type of wire; used for high count straight splicing applications

## **OBSOLETE**

This product was discontinued on: June 1, 2016

### Replaced By

552466-4	PICABOND® Connector, 250 loose piece, 400 Vdc, pink
552466-6	PICABOND® Connector LOOSE PIECE, PINK

## Product Classification

Brand	PICABOND®
Product Series	PICABOND
Product Type	Splice
Regional Availability	Australia/New Zealand   EMEA   Latin America   North America

## Body Features

Cable Insulation Material	Air Core PIC   Paper or Pulp
Color Code	Pink
Sealant	Unfilled

## Contact Features

Contact Base Material	Brass
Contact Plating Material	Tin

## Dimensions

Wire Size (CMA)	28 – 24 AWG
-----------------	-------------

## Electrical Characteristics

Voltage Rating	48 Vdc
----------------	--------

## Packaging Features

Packaging Method	Loose Piece
Packaging Quantity	250

## Product Type Features

---

552466-2

Splicing Applications      High Count Straight

## **Usage Conditions**

---

Operating Temperature    -40 – 60 °C