



DP-25 Series (Pitch 1.25mm)




No. Posi	Part No.	A	B
2	CDP7902-0101	1.25	3.25
3	CDP7903-0101	2.50	4.50
4	CDP7904-0101	3.75	5.75
5	CDP7905-0101	5.00	7.00
7	CDP7907-0101	7.50	9.50
8	CDP7908-0101	8.75	10.75
9	CDP7909-0101	10.00	12.00
10	CDP7910-0101	11.25	13.25
12	CDP7912-0101	13.75	15.75
13	CDP7913-0101	15.00	17.00
15	CDP7915-0101	17.50	19.50




DIP CONNECTOR
ディップコネクタ (1.25mmピッチ)

TERMINAL:CTA 9126-0201
● Applicable Wire Size:AWG 26~32

DP-15 Series (Pitch 1.5mm)



No. Posi	Part No.	A	B
2	CDP5902-0101	1.5	3.7
3	CDP5903-0101	3.0	5.2
4	CDP5904-0101	4.5	6.7
5	CDP5905-0101	6.0	8.2
6	CDP5906-0101	7.5	9.7
7	CDP5907-0101	9.0	11.2
8	CDP5908-0101	10.5	12.7
9	CDP5909-0101	12.0	14.2
10	CDP5910-0101	13.5	15.7
11	CDP5911-0101	15.0	17.2
12	CDP5912-0101	16.5	18.7
13	CDP5913-0101	18.0	20.2
14	CDP5914-0101	19.5	21.7
15	CDP5915-0101	21.0	23.2




DIP CONNECTOR
ディップコネクタ (1.5mmピッチ)

TERMINAL:CTA 9126-0101
● Applicable Wire Size:AWG 26~32

MINIATURE ROUND CONNECTOR (丸形ミニチュアコネクタ)


- Rating:2A 12V DC
- Contact Resistance:30mΩ max.
- Insulation Resistance:50MΩ min. at 250V DC
- Withstanding Voltage:250V AC for one minute

SOCKET




No. Posi	Part No.	Contact Plating
4P	CMS 5004-0302	Silver
	CMS 5004-0303	Gold
6P	CMS 5006-0302	Silver
	CMS 5006-0303	Gold
8P	CMS 5008-0302	Silver
	CMS 5008-0303	Gold

STRAIGHT PLUG




No. Posi	Part No.	Contact Plating
4P	CMC 9004-0401	Silver
	CMC 9004-0402	Gold
8P	CMC 9008-0201	Silver
	CMC 9008-0202	Gold

CMS 5408-0101




CMC 9008-0501



8P CONNECTOR WITH LOCK 8P ロック付コネクタ

- Rating:2A 12V DC
- Contact Resistance:30mΩ max.
- Insulation Resistance:50MΩ min. at 250V DC
- Withstanding Voltage:250V AC for one minute


LLD 1601/1801-0300



6P/8P DIN PLUG CORD 6P/8P DINプラグコード

- Rating:5A 20V DC
- Insulation Resistance:100MΩ min. at 500V DC


LLD 1201/1401-0300



6P/8P DIN PLUG CORD 6P/8P DINプラグコード

- Rating:5A 20V DC
- Insulation Resistance:100MΩ min. at 500V DC


LLD 2601/2801-0300



6P/8P DIN SOCKET CORD 6P/8P DINソケットコード

- Rating:5A 20V DC
- Insulation Resistance:100MΩ min. at 500V DC


LLM 1360-0300



13P PLUG CORD 13Pプラグコード

- Rating:5A 20V DC
- Insulation Resistance:100MΩ min. at 500V DC


LLM 1359-0300



13P PLUG CORD RIGHT ANGLE 13Pプラグコード

- Rating:5A 20V DC
- Insulation Resistance:100MΩ min. at 500V DC


LLF 1356-0300



13P SOCKET CORD 13Pソケットコード


- Rating:5A 20V DC
- Insulation Resistance:100MΩ min. at 500V DC

LAC 1220-0101/0102



13P PLUG SOCKET 13Pプラグソケット


LLC 3001-□□□□



UNIVERSAL CAR PLUG UC-2 ユニバーサルカープラグ UC-2

- Rating:7A 24V DC
- Insertion Force:7kgf max.
- Removal Force:1.0~4.5kgf

LUS 0090-4300



DC-DC CONVERTER (SWITCHING REGULATOR TYPE)

- DC-DCコンバータ (スイッチングレギュレタタイプ)
- Input Voltage:DC 12/24V
- Output Voltage:DC 6.7V
- Current:2A max.

BAR CODE SCANNER

RP2500 Series



BAR CODE PEN SCANNER

- バーコード ペンスキャナ
- 高い焦点深度 (MAX2mm) により、ラミネートなどの被膜されたバーコードの読み取りが可能です。
 - スキャナ電源オートシャットオフ機能付のため、セットの小型、省電力化に寄与します。
 - 読み取り確認用LEDやブザー機能を標準装備しています。