

Low Loss 4-way Wilkinson Splitter, 380 MHz - 2700 MHz 5501.17.0029

Wilkinson Splitter

Description

This Wilkinson style Power Divider has been designed for low power applications where output isolation is preferable over lowest possible loss. The wide frequency range of this design allows use with multiband antennas and leaky cable systems.

Lower loss dividers which enhance receive sensitivity and preserve transmitted power are available as reactive splitters.

Supports Tetra, Tetrapol, LMR/P25, LTE, UMTS/WCDMA, TD-SCDMA, AMPS, GSM, PCS, CDMA, WiFi / WLAN 2.4 GHz.



Technical Data

Electrical Data

Signal Band 1	
Frequency	0.38 - 2.7 GHz
Return Loss input port	17 dB
Return Loss output port	17 dB
Splitter Loss	6 dB
Insertion Loss	7.3 dB
Isol. between Output ports	19 dB
Ampl. tra. betw. outp. ports	0.6 dB
Max. Composite Power	10 W

Input 1	
Connector Type	N
Connector Gender	jack (female)

	Output 1	Output 2	Output 3	Output 4
Connector Type	N	N	N	N
Connector Gender	jack (female)	jack (female)	jack (female)	jack (female)

Char. impedance	50 Ω
-----------------	------

Mechanical Data

Dimensions 19.6 x 118 x 146 mm (Height x Width x Length)
 Weight 0.66 kg

Environmental Data

Environmental conditions indoor
 Operation temperature -30 °C to 60 °C
 Storage temperature -30 °C to 60 °C
 Transport temperature -30 °C to 60 °C
 RoHS 2011/65/EU compliant

Material Data

Piece Parts	Material	Surface Plating
-------------	----------	-----------------

Related Documents

Outline drawing DPR-00172200
 3D-model (Step) DOC-0000369309

Low Loss 4-way Wilkinson Splitter, 380 MHz - 2700 MHz 5501.17.0029

