

MDC-J01F-0500ML

RealFlex® 3 Fiber Optic Drop Cable, SC/APC to stub, RBR Indoor/Outdoor, Ivory, 500 m

Product Classification

Brand	RealFlex®
Product Series	MDC
Product Type	Fiber drop cable assembly
Regional Availability	Latin America North America

Construction Materials

Jacket UV Resistance	UV stabilized
Fiber Type	G.657.A2/B2
Total Fibers, quantity	1
Fiber Mode	Singlemode
Jacket Color	Ivory

Dimensions

Cord Length	500.00 m 1640.42 ft
Diameter Over Jacket	3.00 mm 0.12 in

Environmental Specifications

Environmental Space	Indoor Outdoor
Operating Temperature	-40 °C to +75 °C (-40 °F to +167 °F)
Qualification Standards	Telcordia GR-449-CORE
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)

General Specifications

Interface, connector A	SC
Interface Feature, connector A	APC
Color, boot A	Green
Connector A, quantity	1
Connector B, quantity	0
Package Quantity	1
Transmission Standards	TIA/EIA-568-B.3
Color, connector A	Green
Interface, connector B	Unterminated

Mechanical Specifications

Minimum Bend Radius, loaded	0 in
Minimum Bend Radius, unloaded	1 in

Regulatory Compliance/Certifications

Agency RoHS 2011/65/EU	Classification Compliant
----------------------------------	------------------------------------