



What's New

Interconnect Solutions

Contacts & Modules

High Speed

Industries / Applications

Wired & PCB Solutions

Resources



HOME > CATALOG > 7-232912000-072

[« BACK](#)

7-232912000-072

Power, Patchcord, Receiver, 72", Mini Power, 40 Amps, 12 AWG White, Single Ended



Specifications	
Operating Voltage & Current	40 Amp Max. Continuous - 12 AWG
Contact Resistance	10 mOhms Max.
Mating Force	Insertion - 5.7 lbs. Max. [2.58Kg] Extraction - 5.0 lbs. Max. [2.26Kg]
Dielectric Withstanding Voltage (DWV)	1500 VDC Min.
Insulation Resistance	1000 MOhms Min.
Contact Body	Brass
Contact Plating	50µ" Au over 100µ" Ni
Cycle Life	20,000 Cycles
Wire Type	12 AWG Stranded, M16878/4

[ADD TO QUOTE](#)



Virginia Panel Corporation designs, manufactures and markets interconnect solution products for the automotive, aerospace, defense, medical, and telecommunication industries. VPC is equipped with the latest technology for manufacturing all components of an interface connection system from basic to complex applications. Our personnel are highly trained and motivated with one goal in mind—to provide the customer with the most advanced, high quality product available in the market.

RESOURCES

- User Manuals
- Regulatory Compliances
- White Papers
- Datasheets

COMPANY

- Why Choose VPC?
- About VPC
- Tradeshows
- Careers

CONTACT US

- Request a Quote
- Literature Request
- Contact Your Representative

