

5349569-6 Product Details

[Share](#) |
 [Print](#) |
 [Email](#)



5349569-6

TE Internal Number: 5349569-6
Active

Fiber Optic Cable Assemblies

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Single Fiber
- Cable Assembly
- ST Fiber Optic Cable Connector Type
- Fiber Type = OM2 50/125 Micron
- Cable Assembly Type = ST-Style (2.5mm Bayonet) to Pigtail

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) |
 [Request Sample](#) |
 [Find Similar Products](#) |
 [Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • FOMM50 SIMPLEX 0,9mm ST PIGTAIL (PDF, English) <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

[List all Documents](#)

Feedback

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Product Designation = Single Fiber • Product Type = Cable Assembly • Fiber Optic Cable Connector Type = ST • Cable Assembly Type = ST-Style (2.5mm Bayonet) to Pigtail • Cable Type = Buffered Fiber <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Insertion Loss (dB) = 0.30 <p>Termination Features:</p> <ul style="list-style-type: none"> • Fiber Type (Micron) = OM2 50/125 <p>Dimensions:</p> <ul style="list-style-type: none"> • Cable Diameter (mm [in]) = .9 [.035] • Length (M [ft]) = 3.00 [9.842] <p>Body Features:</p> <ul style="list-style-type: none"> • Cable Color = Green • Boot Body Style - Left = Long • Boot Color - Left = Black • Ferrule Material = Ceramic 	<p>Contact Features:</p> <ul style="list-style-type: none"> • Fibre Channel = No <p>Configuration Features:</p> <ul style="list-style-type: none"> • Mode = Multimode • Number of Fibers = 1 • Cable Buffering = Tight Buffered Easy Strip • Connector(s) Exit Angle to Connector(s) Exit Angle = 180° to Pigtail <p>Industry Standards:</p> <ul style="list-style-type: none"> • Flammability Rating Type = No Jacket • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Not relevant for lead free process • RoHS/ELV Compliance History = Always was RoHS compliant <p>Product Availability:</p> <ul style="list-style-type: none"> • Region = Asia, Latin America, North America <p>Other:</p> <ul style="list-style-type: none"> • Brand = TE Connectivity

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)

Quick Links

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)

Keep Me Informed



[Supplier Portal](#)

[Product Compliance Support Center](#)

[Manage Your Account](#)



[Careers](#)

[Site Map](#)

[Terms & Conditions](#)

[Privacy Policy](#)

[AODA Accessibility Policy](#)

[AODA Multi-Year Accessibility
Plan](#)