

SEMELAB

Type No.	Reliability Option	Polarity	Package	V _{CEO}	I _c cont	h _{FE} @	V _{CE} /I _c	f _T	P _D
BC547A		NPN	TO92	45	0.1	110-220	5/2m	300M	0.5
BC547B		NPN	TO92	45	0.1	200-450	5/2m	300M	0.5
BC547C		NPN	TO92	45	0.1	420-800	5/2m	300M	0.5
BC548		NPN	TO92	30	0.1	450-900	5/2m	300M	0.5
BC548A		NPN	TO92	30	0.1	110-220	5/2m	300M	0.5
BC548B		NPN	TO92	30	0.1	200-450	5/2m	300M	0.5
BC548C		NPN	TO92	30	0.1	420-800	5/2m	300M	0.5
BC549		NPN	TO92	30	0.1	110-800	5/2m	300M	0.5
BC549A		NPN	TO92	30	0.1	110-220	5/2m	300M	0.5
BC549B		NPN	TO92	30	0.1	200-450	5/2m	300M	0.5
BC549C		NPN	TO92	30	0.1	420-800	5/2m	300M	0.5
BC550		NPN	TO92	45	0.1	240-900	5/2m	300M	0.5
BC556		PNP	TO92	65	0.1	75-250	5/2m	150M	0.5
BC557		PNP	TO92	45	0.1	75-250	5/2m	150M	0.5
BC557A		PNP	TO92	45	0.1	125-250	5/2m	150M	0.5
BC557B		PNP	TO92	45	0.1	200-450	5/2m	150M	0.5
BC558		PNP	TO92	30	0.1	75-475	5/2m	150M	0.5
BC558A		PNP	TO92	30	0.1	125-250	5/2m	150M	0.5
BC558B		PNP	TO92	30	0.1	250-475	5/2m	150M	0.5
BC558C		PNP	TO92	30	0.1	420-800	5/2m	150M	0.5
BC559		PNP	TO92	30	0.1	125-475	5/2m	150M	0.5
BC559A		PNP	TO92	30	0.1	125-250	5/2m	150M	0.5
BC559B		PNP	TO92	30	0.1	250-475	5/2m	150M	0.5
BC559C		PNP	TO92	30	0.1	420-800	5/2m	150M	0.5
BC612K		PNP	TO92	70	0.2	60-300	5/2m	200M	0.3
BC612L		PNP	TO92	70	0.2	60-300	5/2m	200M	0.3
BC618L		NPN	TO92	55	1	10k-50k	5/0.2		1.2
BC639		NPN	TO92	80	0.5	40-160	2/0.15	130M	1
BC640		PNP	TO92	80	0.5	40-160	2/0.15	130M	1
BC714L		PNP	TO92	30	0.2	140-600	5/2m	200M	0.3
BC876		NPN	TO92	45	1	1kmin	10/0.15	200M	0.8
BCF33		NPN	TO236	20	0.2	420min	/0.2	300M	0.2
BCF70		PNP	TO236	45	0.2	215min	/0.2	150M	0.2
BCF81		NPN	TO236	20	0.2	420min	/0.2	300M	0.2
BCW29		PNP	TO92	20	50m	120-260	5/10m	150M	0.15
BCW33		NPN		20	50m	420-800	5/2m	300M	0.15
BCW34	HI-REL	NPN	TO18	45	0.6	100-350	5/10m	150M	0.36
BCW35	HI-REL	PNP	TO18	45	0.6	100-350	5/10m	150M	0.36
BCW65		NPN	TO236	32	0.8			100M	0.35
BCW66		NPN	TO236	45	0.8	100-630	1/0.1	100M	0.35
BCY30A	HI-REL	PNP	TO5	64	0.1	10-35	4.5/20m	7M	0.6
BCY31A	HI-REL	PNP	TO5	64	0.1	15-60	4.5/20m	7M	0.6
BCY32A	HI-REL	PNP	TO5	64	0.1	20-70	4.5/20m	7M	0.6
BCY33A	HI-REL	PNP	TO5	32	0.1	10-35	4.5/20m	7M	0.6
BCY34A	HI-REL	PNP	TO5	32	0.1	15-60	4.5/20m	7M	0.6