

S-3-UW-L-NI53

CommScope-Proprietary and Confidential. Preliminary specifications are for illustrative purposes only and will be updated prior to publication.

Three-way Low Power Splitter, 555-6000MHz

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Type	Power splitter

General Specifications

Device Type	Splitter
Application	Indoor/Outdoor
Color	White
Inner Contact Plating	Silver
Interface	N Female
Outer Contact Plating	Trimetal

Dimensions

Height	22.3 mm 0.878 in
Width	98.4 mm 3.874 in
Length	179.8 mm 7.079 in

Electrical Specifications

3rd Order IMD	-153 dBc
3rd Order IMD Test Method	Two +43 dBm carriers
Insertion Loss at Frequency Band	0.6 dB @ 555–2700 MHz 0.9 dB @ 2700–3800 MHz 1.45 dB @ 3800–6000 MHz
Impedance	50 ohm
Isolation Between Bands	17.7 dB
Operating Frequency Band	555 – 6000 MHz
Power Rating, combining	0.125 W
Power Rating, Splitting	30 W
Split Loss	4.8 dB
VSWR	1.3

S-3-UW-L-NI53

Environmental Specifications

Operating Temperature	-25 °C to +85 °C (-13 °F to +185 °F)
Relative Humidity	Up to 100%
Ingress Protection Test Method	IEC 60529:2001, IP65