

Description

The device is a single channel, fixed delay IC. Ultra-compact 2 × 2 mm 8-DFN package with no external reference required with extended temperature operating range.


Typical Applications

- Timing control
- Pulse delay

Features

- Supports 2.5V and 3.3V power supplies
- Multiple input to output delay options based on latched status
 - 100ns delay time setting
 - 75ns delay time setting
- Single channel operation
- -40°C to 105°C operating temperature
- Compact 2 × 2 mm 8-DFN package

Functional Diagram



Contents

1. Pin Assignments.....	3
2. Pin Descriptions.....	3
3. Absolute Maximum Ratings.....	4
4. Thermal Characteristics.....	4
5. Electrical Characteristics	5
6. Output Load Circuit.....	5
7. Package Outline Drawings	6
8. Marking Diagram	6
9. Ordering Information.....	6
10. Revision History.....	6

List of Figures


Figure 1. Pin Assignments for 2 × 2 mm 8-DFN – Top View	3
Figure 2. Single-ended Output Test Load.....	5

List of Tables

Table 1. Pin Descriptions.....	3
Table 2. Absolute Maximum Ratings.....	4
Table 3. Thermal Characteristics.....	4
Table 4. Electrical Characteristics	5

1. Pin Assignments

Figure 1. Pin Assignments for 2 × 2 mm 8-DFN – Top View



2. Pin Descriptions

Table 1. Pin Descriptions

Pin Number	Name	Type	Description
1	VDD	Power	Power supply.
2	NC	–	No Connect.
3	NC	–	No Connect.
4	SEL	Input (Internal Pull-up)	Delay select. When SEL set to high, OUT operates with 75ns T _D setting. When SEL set to low, OUT operates with 100ns T _D setting.
5	OE	Input (Internal Pull-up)	Output Enable for OUT, active high.
6	IN	Input	Input.
7	OUT	Output	Delayed output.
8	GND	Ground	Connect to ground.

3. Absolute Maximum Ratings

The absolute maximum ratings are stress ratings only. Stresses greater than those listed below can cause permanent damage to the device. Functional operation of the device at absolute maximum ratings is not implied. Exposure to absolute maximum rating conditions may affect device reliability.

Table 2. Absolute Maximum Ratings

Symbol	Parameter	Ratings	Units
T_J	Junction Temperature	125	°C
T_S	Storage Temperature	-65 to 150	°C
V_{DD}	Supply Voltage	3.8	V
V_{IN}	Input Voltage (IN, OE, SEL)	V_{DD}	V
	ESD – Charged Device Model	1500	V
	ESD – Human Body Model	2000	V

4. Thermal Characteristics

Table 3. Thermal Characteristics

Symbol	Parameter	Value	Units
θ_{JA}	Theta JA. Junction to air.	88.07	°C/W
θ_{JB}	Theta JB. Junction to board.	15.6	°C/W
θ_{JC}	Theta JC. Junction to case.	175.4	°C/W

5. Electrical Characteristics

$V_{DD} = 3.3V \pm 10\%$, $2.5V \pm 10\%$, $T_A = -40^{\circ}C$ to $105^{\circ}C$

Table 4. Electrical Characteristics

Symbol	Parameter	Conditions	Minimum	Typical	Maximum	Units
$I_{DD}^{[a]}$	Power Supply Current	Output enabled.		4		mA
$I_{DDS}^{[a]}$	Static Supply Current	Output disabled.		3.7		mA
V_{IL}	Input Low Voltage				0.8	V
V_{IH}	Input High Voltage		$0.7 \times V_{DD}$			V
I_{IL}	Input Leakage Current Low	IN.	-5		5	μA
I_{IL}	Input Leakage Current Low	OE, SEL.	-25		-6	μA
I_{IH}	Input Leakage Current High	IN, OE, SEL.	-5		5	μA
V_{OL}	Output Low Voltage	+2mA load.			0.4	V
V_{OH}	Output High Voltage	-2mA load.	$0.7 \times V_{DD}$			V
R_{UP}	Internal Pull-up Resistance	OE, SEL.		250		k Ω
T_D	Delay Time		-10		10	%
T_R	Output Rise Time	20% to 80%.		350		ps
T_F	Output Fall Time	80% to 20%.		300		ps
$T_{WIDTH}^{[b]}$	Pulse Width		17			ns
$T_{PERIOD}^{[c]}$	Minimum Input Period		$T_D/4$			ns


[a] Measured with periodic 1MHz clock signal, rail to rail input.

[b] Measured at 50% of V_{DD} level.

[c] Variation needs to be taken into consideration for different devices across process and temperature. Please refer to parameter T_D specification.

6. Output Load Circuit

Figure 2. Single-ended Output Test Load




7. Package Outline Drawings

The package outline drawings are appended at the end of this document and are accessible from the link below. The package information is the most current data available.

<https://www.renesas.com/us/en/document/psc/8-dfn-package-outline-drawing20-x-20-x-075-mm-body-05mm-pitch-epad-09-x-160-mm-ntg8p1>

8. Marking Diagram




- Line 1 is the truncated part number.
- "YW" is the last digit of the year and work week that the part was assembled.
- "***" denotes sequential lot number.

9. Ordering Information

Orderable Part Number	Description and Package	Carrier Type	Temperature
6T80002NTGK	2 × 2 mm, 0.5mm pitch 8-DFN	Tray	-40°C to +105°C
6T80002NTGK8	2 × 2 mm, 0.5mm pitch 8-DFN	Reel	-40°C to +105°C

10. Revision History

Revision Date	Description of Change
February 7, 2023	Updated POD links and disclaimer.
May 17, 2019	Updated Thermal Characteristics values.
October 3, 2018	Initial release.



RECOMMENDED LAND PATTERN DIMENSION

NOTES:

1. ALL DIMENSIONS ARE IN MM. ANGLES IN DEGREES.
2. TOP DOWN VIEW, AS VIEWED ON PCB.
3. LAND PATTERN RECOMMENDATION PER IPC-7351B GENERIC REQUIREMENT FOR SURFACE MOUNT DESIGN AND LAND PATTERN.

Package Revision History		
Date Created	Rev No.	Description
Feb 12, 2018	Rev 01.	New Format, Change QFN to VFQFPN
April 12, 2018	Rev 02	Change from "VFQFPN" to "DFN"

IMPORTANT NOTICE AND DISCLAIMER

RENESAS ELECTRONICS CORPORATION AND ITS SUBSIDIARIES (“RENESAS”) PROVIDES TECHNICAL SPECIFICATIONS AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for developers skilled in the art designing with Renesas products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. Renesas grants you permission to use these resources only for development of an application that uses Renesas products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Renesas intellectual property or to any third party intellectual property. Renesas disclaims responsibility for, and you will fully indemnify Renesas and its representatives against, any claims, damages, costs, losses, or liabilities arising out of your use of these resources. Renesas' products are provided only subject to Renesas' Terms and Conditions of Sale or other applicable terms agreed to in writing. No use of any Renesas resources expands or otherwise alters any applicable warranties or warranty disclaimers for these products.

(Disclaimer Rev.1.0 Mar 2020)

Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,
Koto-ku, Tokyo 135-0061, Japan
www.renesas.com

Contact Information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit:
www.renesas.com/contact/

Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.