



ELECTRICAL:

CURRENT RATING: 1A

CONTACT RESISTANCE:

< 15m Ω Max.

INSULATOR RESISTANCE:

> 1000M Ω Min.

DIELECTRIC WITHSTANDING VOLTAGE:

1000VAC for 1 Minute

OPERATING TEMPERATURE: -55° C to +105° C

MATERIAL:

INSULATOR: Thermoplastic UL94V-0

CONTACTS: Phosphor Bronze

TERMINAL: Copper Alloy

FINISH: Selective plating in contact area, 150u" Min.

Tin on solder tail, Both over 50u" Min.

Nickel Underplated.

SHELL: Copper Alloy

FINISH: 100u" Tin

HOW TO ORDER:

U 0 0 3 - 0 5 7 X - X 0 X - Z X

NUMBER OF CONTACTS:

04 - 4 PIN SINGLE PORT

BODY STYLE:

7 - 9.9 X 9.2 Mini A/B

SHELL STYLE:

1 - With Tape on

Shield (Top)

2 - Without Tape

INSULATOR COLOR:

0 - BLACK

1 - WHITE

MOUNTING STYLE:

0 - With Mounting Peg

(4.4 between pegs)

**RoHS
COMPLIANT**

PACKAGING:

BLANK - T/R

1 - Tray

2 - Tube

SELECTIVE CONTACT PLATING:

1 - Gold

3 - 15u" Gold

4 - 30u" Gold

Rev		Apv.	Date
0	Issued	S.E.	10/1/97
A	Revised Shell Style	WHS	7/11/06
SCALE	MAT'L	FINISH	
TOL. DEC.	.X +/- 0.35	.XX +/- 0.25	.XXX +/-
		ANGLE +/-	UNIT: mm

SMP TECHNOLOGY, INC.	
Mini A/B USB Connector, Single Port, Right Angle, Surface Mount	
P/N : U 0 0 3 - 0 5 7 X - X 0 X - Z X	Pg: 1