



[> Characteristic value search](#)
[> Distributor inventory search](#)

LC-P1220J: LC Series



Series / Type : LC Series
part number : LC-P1220J

[FIND INVENTORY OF LC-P1220J](#)
[Electronic devices and industrial equipment](#)
[Top of Page](#)
[FAQs](#)
[Inquiries about the product](#)

[Please be sure to read the notes at the beginning](#)

Characteristic value

item	Content
Nominal voltage	12 V
Rated capacity (20 hour rate)	20 Ah
Nominal capacity (of 10 minutes)	-
type	Main power supply and backup shared
Trickle life expectancy (year / 25 °C)	6 years
-	- Year
length	181 mm
width	76 mm
height	167 mm
Total height	167 mm
mass	6.2 kg
Terminal shape	M5 bolts and nuts
Battery container material	Flame retardant (UL94V-0)

Related information

[LC-P1220J catalog]

 [Catalog \(483KB\)](#)

[Valve regulated lead-acid batteries common information]

 [Safety Precautions \(417KB\)](#)

 [Characteristics of the control valve type lead-acid battery \(431KB\)](#)

 [Selection of the battery \(496KB\)](#)

 [For the pin shape \(435KB\)](#)

 [Battery replacement of UPS is planned \(413KB\)](#)

 [Control valve type lead-acid battery Glossary \(270KB\)](#)

 [Overview of the control valve type lead-acid battery \(641KB\)](#)

 [Charging \(500KB\)](#)

 [For safety / transport / domestic and international standard acquisition \(235KB\)](#)

 [For replacement of the battery \(413KB\)](#)

 [Processing method of used lead-acid batteries \(85KB\)](#)

[Notes of our products](#)