

ピンダイオードスイッチ

PIN Diode Switches

形名 Type	周波数 Frequency (MHz)	そう入損失 Insertion Loss (dB max.)	アイソレーション Isolation (dB min.)	電圧定在波比 V.S.W.R. (max.)	耐電力 Rating Power (kW max.)	備考 Remarks
NJS6106	30-40	0.3	70	1.1	—	SPDT
NJS6107	100-160	0.3	70	1.1	—	SPDT
NJS6103	120-160	0.3	55	1.05	—	SPDT
NJS6104	260-300	0.3	50	1.05	—	SPDT
NJS6105	380-420	0.3	45	1.05	—	SPDT
NJS6111	700-800	0.8	70	1.3	—	SPDT
NJS6401	3400-3800	1.4	50	1.5	—	SPDT
NJS6506	5400-5600	0.7	20	1.3	—	SPDT
NJS6507	5000-5100	0.7	40	1.3	—	SPDT
NJS6926	9300-9500	0.6	25	1.5	—	—
NJR6208	16600-16900	2.5	60	1.5	10	—
NJR6209	16600-16900	1.5	25	1.5	10	—
NJR6218	16600-16900	2	52	1.5	10	—
NJR6219	16600-16900	1.3	25	1.5	10	—

*Other ranges of frequency are also available upon request.

