



Main

Range of product	Acti 9
Product or component type	Residual current circuit breaker (RCCB)
Device short name	RED
Protection type	Recloser
Poles description	2P
Neutral position	Left
[In] rated current	25 A
Earthing system	TN-S TT
Network type	AC
Earth-leakage sensitivity	30 mA

Complementary

Device location in system	Outgoer
Network frequency	50 Hz
[Ue] rated operational voltage	230 V AC 50 Hz phase to neutral
Reset	Fault reset earth leakage
Test function	Manual at 100 V
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type A
Minimum leakage resistance	70 kOhm at operating 20 kOhm at non-operating
[Im] rated making and breaking capacity	Idm 630 A 230 V
Rated conditional short-circuit current	Inc: 6 kA - associated with DPN, 40 A Inc: 6 kA - associated with DPNN, 40 A Inc: 6 kA - associated with iC60N, 25 A Inc: 6 kA - associated with iC60H, 25 A Inc: 6 kA - associated with iC60L, 25 A Inc: 6 kA - associated with NG125, 25 A Inc: 6 kA - associated with gG fuse, 25 A
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 kV
Control type	Toggle

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Local signalling	1 red LED Recloser : ON/OFF indication Residual current device : ON/OFF indication
Operating mode	Reclosing time: 90 s Maximum operational frequency: 15/hour Max nb of consecutive restart: 3 Min interval between 2 closings: 180 s Insulation fault presence monitoring Stopping restart cycle if insulation fault present Restart in event of transient insulation fault
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	8
Height	115 mm
Width	71 mm
Depth	79.5 mm
Mechanical durability	1000 cycles open-close
Connections - terminals	Guard tunnel terminal35 mm ² rigid Guard tunnel terminal25 mm ² flexible
Auxiliary connection terminal	Tunnel type terminal in 2.5 mm ² flexible Tunnel type terminal in 2.5 mm ² rigid
Wire stripping length	12 mm
Tightening torque	2 N.m

Environment

Standards	EN 61008 IEC 61008
IP degree of protection	IP20
Electromagnetic compatibility	8/20 µs wave immunity, 250 A
Tropicalisation	2
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-20...60 °C

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------