



### Main

Range	Linergy
Range of product	Linergy
Product or component type	Distribution block
Product name	Linergy DX
Range compatibility	Prisma G enclosure Prisma P enclosure Prisma PH enclosure Prisma Pack 160 enclosure Prisma Pack 250 enclosure
Accessory / separate part category	Current distribution accessory
IP degree of protection	IPxx B

### Complementary

Mounting support	DIN rail
Installed device	Acti 9: fixed C120 with earth leakage protection - control: toggle Acti 9: fixed C120 without earth leakage protection - control: toggle Acti 9: fixed iC120 with earth leakage protection - control: toggle Acti 9: fixed iC120 without earth leakage protection - control: toggle ComPact: fixed INS40 - control: direct front rotary handle - vertical installation ComPact: fixed INS63 - control: direct front rotary handle - vertical installation ComPact: fixed INS100 - control: direct front rotary handle - vertical installation ComPact: fixed INS125 - control: direct front rotary handle - vertical installation ComPact: fixed INS160 - control: direct front rotary handle - vertical installation Multi 9: fixed NG125 with earth leakage protection - control: toggle Multi 9: fixed NG125 without earth leakage protection - control: toggle Multi 9: fixed NG125 NA - control: toggle ComPact: fixed NG160 with earth leakage protection - control: toggle ComPact: fixed NG160 without earth leakage protection - control: toggle ComPact: fixed NG160 NA without earth leakage protection - control: toggle ComPact: fixed NSXm without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSXm with earth leakage protection - control: toggle - vertical installation
Poles description	4P
[Ue] rated operational voltage	690 V AC
[Ui] rated insulation voltage	750 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	125 A at 40 °C
[Icw] rated short-time withstand current	4.5 kAfor 1 s
[Ipk] rated peak withstand current	20 kA
I <sup>2</sup> t on activation	20250000 A <sup>2</sup> .s
Connections - terminals	Supply: tunnel type terminal35 mm <sup>2</sup> (rigid) Supply: tunnel type terminal35 mm <sup>2</sup> (flexible) Distribution: spring terminal, 2 x 4...10 mm <sup>2</sup> (flexible) Distribution: spring terminal, 2 x 4...10 mm <sup>2</sup> (rigid) Distribution: spring terminal, 3 x 2.5...6 mm <sup>2</sup> (flexible) Distribution: spring terminal, 3 x 2.5...6 mm <sup>2</sup> (rigid) Distribution: spring terminal, 7 x 1.5...4 mm <sup>2</sup> (flexible) Distribution: spring terminal, 7 x 1.5...4 mm <sup>2</sup> (rigid) Distribution: tunnel type terminal, 1 x 4...16 mm <sup>2</sup> (flexible) Distribution: tunnel type terminal, 1 x 4...25 mm <sup>2</sup> (rigid)
9 mm pitches	12
Height	127 mm
Width	108 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Depth	48 mm
Net weight	0.5 kg
Colour	Anthracite grey (RAL 7016)

## Environment

Pollution degree	3
Resistance to incandescent wire	960 °C conforming to IEC 60695-2-11
Standards	IEC 60947-7-1 IEC 61439-1, inside Prisma IEC 61439-2, inside Prisma
Product certifications	ASEFA
Ambient air temperature for operation	-25...55 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	500 g
Package 1 Height	9.8 cm
Package 1 width	11.2 cm
Package 1 Length	13.5 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	5
Package 2 Weight	2.58 kg
Package 2 Height	12 cm
Package 2 width	15 cm
Package 2 Length	50 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	5
Package 3 Weight	2.58 kg
Package 3 Height	12 cm
Package 3 width	15 cm
Package 3 Length	50 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------