

RM243 Product Details



Industrial Panel Mount Switches and Lights

[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Switch
- Switch Type = Keylock
- Operating Function = Maintained
- Cam = 4
- Contact Rating = 6A

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

RM243

(6-1437614-4)

TE Internal Number: 6-1437614-4



Obsolete

[Contact Product Information Center](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • ALCOSWITCH PRODUCTS (PDF, English) <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Product Type = Switch • Actuator Style = Key • Number of Positions = 3 • Frame Style = Front Beveled • Comment = Contact Blocks Not Supplied, Order Separately <p>Mechanical Attachment:</p> <ul style="list-style-type: none"> • Panel Cutout = 22mm Diameter <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Cam = 4 • Contact Rating = 6A • Oil-Tight = Yes <p>Termination Related Features:</p> <ul style="list-style-type: none"> • Seal Type = IP65 <p>Body Related Features:</p> <ul style="list-style-type: none"> • Switch Type = Keylock • Series = Reliant'22 • Actuator Profile = Extended • Bushing Material = Heavy-Duty Metal • Used With = Alternate Action Maintained Contacts, Electronic Duty Contact Blocks, Quick Connect Contact Blocks, Screw Terminal Contact Blocks • Mount Style = Panel 	<p>Contact Related Features:</p> <ul style="list-style-type: none"> • Approved Standards = NEMA 1, 12 and 13 <p>Housing Related Features:</p> <ul style="list-style-type: none"> • Remove Key = Position 1 or 3 • Bushing Style = Bayonet <p>Configuration Related Features:</p> <ul style="list-style-type: none"> • Operating Function = Maintained • Number of Actuators = Single • Illuminated = No • Frame Color = Black <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Not relevant for lead free process • RoHS/ELV Compliance History = Always was RoHS compliant <p>Other:</p> <ul style="list-style-type: none"> • Brand = Alcoswitch