



SPECIFICATION:
ELECTRICAL

- 1. RATING: 100V AC 2A
- 2. CONTACT RESISTANCE: 20m OHM MAX.
- 3. INSULATION RESISTANCE: 300M OHM MIN. AT DC 500V
- 4. VOLTAGE WITHSTANDING: AC 1000V FOR ONE MINUTE

MECHANICAL

- 1. INSERTION FORCE: 6.5KGS MAX.
- 2. WITHDRAWAL FORCE: 1-5KGS

ARRANGEMENT OF CONTACTS	72°	60°	45°	45°
MODEL NO.	DJ-D-04	DJ-D-06	DJ-D-07	DJ-D-08
HOLE LAYOUT				

P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS
5.	RIVET	1	AL	NICKEL PLATED	
4.	CONTACT TERMINAL	8	BRASS 0.7t	Pb10%, Sn90%	
3.	EARTH TERMINAL	1	PBSR-H 0.25t	Pb10%, Sn90%	
2.	INSULATOR	1	P.B.T.	VALOX 420-SEO	UL94V-0
1.	SOCKET CASE	1	SPCC-SD 0.4t	NICKEL PLATED	

DJ-D-xx-LF
LEADFREE

RoHS Compliant



PART NO. DJ-D-xx

DWG NO. DJ-D-xx

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2
.XX ± 0.1
.XXX ±
AWG

DESCRIPTION:

AREA

REVISIONS

HK

DATE

焯倫股份有限公司