


**SPECIFICATIONS**

Voltage rating: 125VAC/VDC  
 Current rating: AWG 24, 2.0 amps  
 AWG 26, 1.5 amps  
 AWG 28, 1.0 amp  
 Housing material: Phosphor bronze  
 Contact resistance: 20 milliohms max.  
 Contact resistance (crimp): 5 milliohms max.  
 Contact plating: Tin  
 Insulation diameter: ø1.4mm max.  
 Withstanding: 500VAC for 1 min.  
 Temperature range: -40°C to +105°C  
 Terminal thickness: 0.2mm

RoHS compliant

| Rev. | Description | Date | Approved | Drawing  | Name        | Date        |
|------|-------------|------|----------|--|-------------|-------------|
|      |             |      |          | Approved   | Howard      | 06/30/06    |
|      |             |      |          | Checked  | Lizzy       | 06/30/06    |
|      |             |      |          | Drawn  | Tina        | 06/30/06    |
|      |             |      |          | 0.0 ± 0.35   | 0.00 ± 0.20 | Angles ± 3' |
|      |             |      |          |  UNIT: mm |             |             |


**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-A-9513-LF**

Description: Wire-to-wire female crimp terminal, .079" (2.0mm) pitch