



# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDD-525-001 REV: 1.2

## 0.54" Dual Digit Alphanumeric Displays

MODEL NO : ELD-525GWA ECN :            Page: 1/5

### ■ Features :

- Industrial standard size.
- Low power consumption.
- Categorized for luminous intensity.

### ■ Applications:

- Audio equipment
- Instrument panels
- Digital read out display

### ■ Descriptions :

- The ELD-525 series is a large 13.6mm (0.54")high seven segment display designed for viewing distances up to 7 meters.
- These displays provide excellent reliability in bright ambient light.
- These devices are made with white segments and gray surface.

PART NO	Chip		C.C. or C.A.
	Material	Emitted Color	
ELD-525GWA	GaP	Green	C.C.

OFFICE : NO. 25,Lane 76,Sec.3, Chung Yang Rd., Tucheng 236, Taipei, Taiwan, R.O.C.

TEL : 886-2-2267-2000,2267-9936

FAX : 886-2-2267-6244,22676189,22676306





<http://www.everlight.com>




## 0.54" Dual Digit Alphanumeric Displays

MODEL NO : ELD-525GWA ECN : \_\_\_\_\_ Page: 2/5

### Package Dimensions:



- COMMON CATHODE**
- 1 ANODE E
  - 2 ANODE N
  - 3 NO CONNECT
  - 4 ANODE M
  - 5 ANODE L
  - 6 ANODE G2
  - 7 ANODE D
  - 8 ANODE DP
  - 9 ANODE C
  - 10 ANODE B
  - 11 COMMON CATHODE DIG.2
  - 12 ANODE A
  - 13 ANODE G1
  - 14 ANODE K
  - 15 ANODE J
  - 16 COMMON CATHODE DIG.1
  - 17 ANODE H
  - 18 ANODE F



### Notes:

1. All dimensions are in millimeters, tolerance is 0.25mm unless otherwise noted.
  2. Above specification may be changed without notice.
- Supplier will reserve authority on material change for above specification.

Device Number : DDD-525-001 REV: 1.2

## 0.54" Dual Digit Alphanumeric Displays

MODEL NO : ELD-525GWA ECN :                      Page: 3/5

### ■ Absolute maximum ratings at Ta = 25°C :

Parameter	Symbol	Rating	Unit
Reverse Voltage	Vr	5	V
Forward Current	If	30	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Power Dissipation	Pd	100	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	If(Peak)	160	mA

### ■ Electronic optical characteristics :

Parameter		Symbol	MIN.	TYP.	MAX.	Unit	Condition
Luminous Intensity	Per segment	Iv	1.40	2.00	----	mcd	If=10mA
	Per decimal point		0.45	0.75	----	mcd	If=10mA
Peak Wavelength		$\lambda p$	----	565	----	nm	If=20mA
Dominant Wavelength		$\lambda d$	----	570	----	nm	If=20mA
Spectrum Radiation Bandwidth		$\Delta \lambda$	----	30	----	nm	If=20mA
Forward Voltage		Vf	1.7	2.1	2.4	V	If=20mA
Reverse Current		Ir	----	----	10	$\mu A$	Vr=5V



# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDD-525-001 REV: 1.2

0.54" Dual Digit Alphanumeric Displays

MODEL NO : ELD-525GWA ECN : \_\_\_\_\_ Page: 4/5

## Reliability test items and conditions:

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min ∫ 5 min L : -55°C 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min ∫ 10 sec L : -10°C 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	If = 10 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C /85% RH	1000 HRS	76 PCS	0/1



# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDD-525-001 REV: 1.2

0.54" Dual Digit Alphanumeric Displays

MODEL NO: ELD-525GWA ECN :                      Page: 5/5

## ■ Typical Electro-Optical Characteristic Curves:

