





Metric  



Home page > **PLUG SHV5**



PLUG SHV5

SHV 5 kV, accessories | 100580

number of contacts	1
tension	5kV DC

 Show Technical Draft

€30.00

Available



Metric  [CUSTOMER SERVICE](#)DETAILS **category**

SHV 5 kV, accessories

cable connection

jam

strain relief

Yes

info text

Air-side 5 kV SHV connector,
housing: brass, nickel-plated,
contact: bronze alloy, gold-plated, for soldering
Suitable for coaxial cables RG58, RG142, RG400, RG223
cable shield for clamping,
temperature range: -65°C - 165°C

max bakeout temperature

165°C

Article no.

100580

number of contacts

1

maximum voltage

5kV DC



Metric  

umbrella	not specified
connector	not specified
Material housing/weld adapter	brass (nickel-plated)
Material insulation	PTFE
Material contact(s)	copper alloy
contact coating	gold plating
minimum operating temperature	-65°C
maximum operating temperature	165°C
outer diameter	14.5mm
length	44.8mm
Key-width	9.5mm

Haven't found the right product for your application?

We would be happy to advise you on other electrical feedthroughs that are currently not available in our shop.



Metric  



CONTACT US

Contact

FAQ

LEFT

Home page

Know-how

Products

Career

product catalogue

SOCIAL MEDIA

 Xing

 Instagram

 Facebook

 LinkedIn

 YouTube



©VACOM 2022 All rights reserved

[imprint](#)

[privacy](#)

[Conditions](#)

[gender note](#)