



**.240 Square Spade
.031 Electro-Tinned Copper
16-14 AWG (Blue)**

**Spade and Ring Series
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.147	.200	.250						
0	X			B	✓	✓	4000	50083	
		X		B	✓	✓	3000	50083-8	
			X	B	✓	*	3000	50083-8A	
	X			W	✓	✓	4000	50084	
		X		W	✓	✓	3000	50084-8	
			X	W	✓	*	3000	50084-8A	
2	X			B	✓	✓	4000	50091	
		X		B	✓	✓	3000	50091-8	
			X	B	✓	*	3000	50091-8A	
	X			W	✓	✓	4000	50092	
		X		W	✓	✓	3000	50092-8	
			X	W	✓	*	3000	50092-8A	
4	X			B	✓	✓	4000	50099	
		X		B	✓	✓	3000	50099-8	
			X	B	✓	*	3000	50099-8A	
	X			W	✓	✓	4000	50100	
		X		W	✓	✓	3000	50100-8	
			X	W	✓	*	3000	50100-8A	
6	X			B	✓	✓	4000	50107	
		X		B	✓	✓	3000	50107-8	
			X	B	✓	*	3000	50107-8A	
	X			W	✓	✓	4000	50108	
		X		W	✓	✓	3000	50108-8	
			X	W	✓	*	3000	50108-8A	

**.300 Square Spade
.020 Pre-Tinned Brass
16-14 AWG (Blue)**

**Spade and Ring Series
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.147	.200	.250						
4	X			B	✓	✓	4000	50265-200	
		X		B	✓	✓	3000	50265-200-8	
			X	B	✓	*	3000	50265-200-8A	
6	X			B	✓	✓	4000	50277-200	
		X		B	✓	✓	3000	50277-200-8	
			X	B	✓	*	3000	50277-200-8A	
8	X			B	✓	✓	4000	50289-200	
		X		B	✓	✓	3000	50289-200-8	
			X	B	✓	*	3000	50289-200-8A	
10	X			B	✓	✓	4000	50301-200	
		X		B	✓	✓	3000	50301-200-8	
			X	B	✓	*	3000	50301-200-8A	

Recommended Strip Length $\frac{9}{32} \pm \frac{1}{32}$
* Contact Factory for Latest Agency Approvals.

**G
N
I
R
&
E
D
A
P
S**