



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1 BRASS PER QQ-B-626
- 2 BRASS PER QQ-B-613
- 3 NICKEL PL. 80 MIN. THICK OVER COPPER STRIKE
- 4 NICKEL PL. 80 MIN. THICK OVER COPPER PL. 300 MIN. THICK
- 5 PHOSPHOR BRONZE PER QQ-B-750
- 6 GOLD FLASH OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 7 ZINC DIECAST

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
6	HEX NUT			1	HN14-1/2-28X25
5	LOCK WASHER			1	LW-15B/13X05
4	CONTACT PIN			1	B6251G1-NPP3G
3	INSULATOR	P.P.	NATURAL		-50-G
2	BODY				
1	HOUSING	PBT	WHITE		

DIMENSIONS ARE IN MILLIMETERS				PART NO.			
UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4				B6251G1-NPP3G-50			
				APPROVED	DATE	10-11-01'	
				CHECKED	DATE	10-11-01'	
				DRAWN	DATE	10-11-01'	
SCALE	2.5/1	ISSUE	A	FILE NO.			

**Amphenol**

TITLE  
BNC STRAIGHT PC MOUNT RECEPT. JACK

DRAWING NO.  
KJ-B6251G1-NPP3G-50

ITEM NO.