




</

1- Nominal frequency (Fo)	:	20 MHz
Initial tolerance after shipment (after frequency recovery)	:	Fo ± 5E-7
2- Power Supply Voltage supply	:	+ 3.3 V ± 5 %
2.1- Power consumption @ warm-up time	:	≤ 3.5 W
2.2- Current in steady state +25°C	:	≤ 1.5 W
3- Output signal into 15pF load (rating up to 3 loads, CI = 15 pF)		HCMOS compatible
3.1- Output levels		Voh ≥ +2.4V / Vol ≤ +0.4 V
3.2- Duty cycle @ 50% output signal	:	50 ± 10%
3.3- Rise - Fall times (from 10 to 90% output signal)	:	≤ 5 ns 15pF load)
3.4- Phase noise (in dBc/Hz) @ 1 Hz offset	:	- 80 typical
@ 10 Hz	:	- 110 typ.
@ 100 Hz	:	- 135 typ.
@ 1 kHz	:	- 145 typ.
@ 10 kHz & over	:	- 150 typ.
4- Frequency stability over operating conditions – all causes inclusive,		
Total free-run accuracy (Telcordia GR-1244 requirement : +/-4.6 ppm)	:	≤ ± 2 E-6 over lifetime
<i>after frequency recovery : required time of continuous operation so as to re-stabilize the device after powered-off / storage period)</i>		
4.1-ageing – stability versus time		≤ ± 5E-10/day / ≤ ± 8E-8/year
extrapolated for for 20 years		≤ ± 8E-7
4.2- Drift 24 hours with ± 2.8°C (per Telcordia GR 1244)	:	≤ ± 8E-10
4.3- Short term 1s integration time – 100 samples	:	1 E-11 typical
4.4- Stability over -20°C to + 70°C calm air	:	≤ ± 10 ppb
4.5- versus voltage (± 5%)	:	≤ ± 3E-9
4.6- Warm-up time @ +25°C to within ± 1E-7 of frequency reference	:	≤ 5 mn (2 mn typ.)
(with frequency reference = frequency reached by the device after 24h on)		
4.7- Wander generation value under following tests conditions		
- Oscillator stabilised 24 hours at constant temperature		
- Data collection during 100,000 seconds at 1s interval		
- Frequency data subjected to a 1mHz loop filter		
(-3dB cut-off frequency, 2 nd order high pass filter)		
- MTIE (GR-1244/ Fig 5-5)	:	≤ 100 ns
- TDEV (GR-1244/ Fig 5-4)	:	≤ 10 ns
5- Environmental conditions (not operating – qualification)		
5.1- Vibration 10g; 10- 500 Hz		IEC 68-2-6 test Fc severity 500/10
5.2- Shocks 50g – 11ms -1/2 sine		IEC 68-2-27 test Ea severity 50A
5.3- Storage temperature range		from - 50°C / + 90°C
6-Marking / Printed label on top of lid		RAKON
Part Number ("LF" means "RoHS")		STP2885 LF
Nominal Frequency		20 MHz
Serial Number	SN	L Nnnnn
Manufacturing date code (Year & Week)	DC	Yy Ww

rakon 44 avenue de la Glacière - BP 165 95105 ARGENTEUIL CEDEX - FRANCE Tel. : +33 (0) 1 3998 3600 E_mail : <i>Firstname.Surname@rakon.com</i> Fax : +33 (0) 1 3998 3660	OCXO SPECIFICATION	Reference	Page	2/5
		STP 2885 LF	Date	Visa
			2010 October. 18th.	<i>Cyril Datin & Philippe Bunel</i>
RoHS SMD OCXO / CFPO-11 @ 20 MHz _ 3.3V SUPPLY <i>+/-10 PPB OVER -20°C TO +70°C _ 12 MM HIGH MAX</i> Compliant to STRATUM 3E per GR-1244-CORE			<i>ARG NPE 2010-5327</i> Added the Telcordia requirements the 15-10-2010	



1	Not to be connected
2	Not to be connected
3	Supply voltage
4	RF Output signal
5	Not to be connected
6	Not to be connected
7	Ground (Mechanical & Supply)




Outline Drawing (**maximum overall height of 12.0mm**)

RoHS SMD OCXO / CFPO-11 @ 20 MHz _ 3.3V SUPPLY
+/-10 PPB OVER -20°C TO +70°C _ 12 MM HIGH MAX
Compliant to STRATUM 3E per GR-1244-CORE

ARG NPE 2010-5327


Added the Telcordia
requirements the 15-10-2010

Prole Feature	Pb-Free Assembly
Average Ramp-Up Rate ($T_{s \max}$ to T_p)	3 °C/second max.
Preheat - Temperature Min ($T_{s \min}$) - Temperature Max ($T_{s \max}$) - Time ($t_{s \min}$ to $t_{s \max}$)	150 °C 200 °C 60-1 80 seconds
Time maintained above: - Temperature (T_L) - Time (t_L)	217 °C 60-1 50 seconds
Peak/Classification Temperature (T_p)	245°C
Time within 5 °C of actual Peak Temperature(t_p)	20-40 seconds
Ramp-Down Rate	6 °C/second max.
Time 25 °C to Peak Temperature	8 minutes max.



rakon 44 avenue de la Glacière - BP 165 95105 ARGENTEUIL CEDEX - FRANCE Tel. : +33 (0) 1 3998 3600 E_mail : <i>Firstname.Surname@rakon.com</i> Fax : +33 (0) 1 3998 3660	OCXO SPECIFICATION	Reference	Page	5/5
		STP 2885 LF	Date	Visa
			2010 October. 18th.	<i>Cyril Datin & Philippe Bunel</i>
RoHS SMD OCXO / CFPO-11 @ 20 MHz _ 3.3V SUPPLY <i>+/-10 PPB OVER -20°C TO +70°C _ 12 MM HIGH MAX</i> Compliant to STRATUM 3E per GR-1244-CORE				
			<i>ARG NPE 2010-5327</i>	
			Added the Telcordia requirements the 15-10-2010	

Tape & Reel Packaging : compliant ot standard EIA 481-3



P1	W	Quantity per reel	Diameter
28	44	200	330 mm