

VTMA1ULA Product Details



VTMA1ULA
(2-1437482-2)

TE Internal Number: 2-1437482-2

Active

Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- VTMA1 On-Delay Timing Module with Potentiometer Series
- Input Voltage = 24 - 240 VAC
- Input Voltage = 24 - 240 VDC
- Contact Arrangement = 1 Form A, SPST-NO, 1 N/O Solid State
- Contact Rating = 1A

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Additional Product Images:</p> <ul style="list-style-type: none"> • Wiring Diagram <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Termination Type = .250 x .032 Quick Connect Terminals <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Input Voltage (VAC) = 24 - 240 • Input Voltage (VDC) = 24 - 240 • Contact Rating = 1A <p>Body Related Features:</p> <ul style="list-style-type: none"> • Series = VTMA1 On-Delay Timing Module with Potentiometer <p>Contact Related Features:</p> <ul style="list-style-type: none"> • Mounting Options = Mounting Holes • Mode of Operation = On-Delay • Delay Time = 24 seconds to 480 seconds • Type of Control = Potentiometer Adjustable • Repeatability, Max. = +5% • Approved Standards = CSA Certified, UL Recognized • Approx. Dimensions (L x W x H) (mm [in]) = 50.80 x 50.80 x 22.48 [2.001 x 2.001 x .885] 	<p>Configuration Related Features:</p> <ul style="list-style-type: none"> • Contact Arrangement = 1 Form A, SPST-NO, 1 N/O Solid State • Multiple Timing Ranges = Without <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = Not ELV/RoHS compliant • Lead Free Solder Processes = Not suitable for lead free processing <p>Conditions for Usage:</p> <ul style="list-style-type: none"> • Temperature Range (?C) = -40 - +65 <p>Other:</p> <ul style="list-style-type: none"> • Brand = Agastat

Corporate Information

- [Who We Are](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

Quick Links

- [Check Distributor Inventory](#)
- [Cross Reference](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat with Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)