



"Low Side Chopper" IGBT MTP (Ultrafast Speed IGBT), 100 A



MTP

FEATURES

- Generation 4 ultrafast speed IGBT technology
- HEXFRED® diode with ultrasoft reverse recovery
- Very low conduction and switching losses
- Optional SMD thermistor (NTC)
- Al₂O₃ DBC
- Very low stray inductance design for high speed operation
- UL approved file E78996 
- Speed 8 kHz to 60 kHz > 20 kHz hard switching, > 200 kHz resonant mode
- Compliant to RoHS Directive 2002/95/EC
- Designed and qualified for industrial level



PRODUCT SUMMARY	
V _{CES}	600 V
I _C DC	100 A
V _{CE(on)}	1.68 V

BENEFITS

- Optimized for welding, UPS and SMPS applications
- Low EMI, requires less snubbing
- Direct mounting to heatsink
- PCB solderable terminals
- Very low junction to case thermal resistance

ABSOLUTE MAXIMUM RATINGS					
PARAMETER	SYMBOL	TEST CONDITIONS	MAX.	UNITS	
Collector to emitter voltage	V _{CES}		600	V	
Continuous collector current	I _C	T _C = 25 °C	100	A	
		T _C = 122 °C	50		
Pulsed collector current	I _{CM}		200		
Peak switching current	I _{LM}		200		
Diode continuous forward current	I _F	T _C = 100 °C	48		
Peak diode forward current	I _{FM}		200		
Gate to emitter voltage	V _{GE}		± 20	V	
RMS isolation voltage	V _{ISOL}	Any terminal to case, t = 1 minute	2500		
Maximum power dissipation	P _D	IGBT	T _C = 25 °C	W	
		Diode	T _C = 100 °C		175
			T _C = 25 °C		205
			T _C = 100 °C		83



ELECTRICAL SPECIFICATIONS ($T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified)						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Collector to emitter breakdown voltage	$V_{(BR)CES}$	$V_{GE} = 0\text{ V}, I_C = 250\text{ }\mu\text{A}$	600	-	-	V
Collector to emitter voltage	$V_{CE(on)}$	$V_{GE} = 15\text{ V}, I_C = 50\text{ A}$	-	1.69	2.31	
		$V_{GE} = 15\text{ V}, I_C = 100\text{ A}$	-	1.96	2.55	
		$V_{GE} = 15\text{ V}, I_C = 100\text{ A}, T_J = 150\text{ }^\circ\text{C}$	-	1.88	2.24	
Gate threshold voltage	$V_{GE(th)}$	$I_C = 0.5\text{ mA}$	3	-	6	
Diode reverse breakdown voltage	V_{BR}	$I_R = 200\text{ }\mu\text{A}$	600	-	-	
Temperature coefficient of threshold voltage	$\Delta V_{GE(th)}/\Delta T_J$	$V_{CE} = V_{GE}, I_C = 500\text{ }\mu\text{A}$	-	- 13	-	mV/ $^\circ\text{C}$
Forward transconductance	g_{fe}	$V_{CE} = 50\text{ V}, I_C = 100\text{ A}$	22	29	-	S
Collector to emitter leaking current	I_{CES}	$V_{GE} = 0\text{ V}, V_{CE} = 600\text{ V}$	-	-	0.25	mA
		$V_{GE} = 0\text{ V}, V_{CE} = 600\text{ V}, T_J = 150\text{ }^\circ\text{C}$	-	-	6	
Diode forward voltage drop	V_{FM}	$I_F = 100\text{ A}, V_{GE} = 0\text{ V}$	-	1.64	1.82	V
		$I_F = 100\text{ A}, V_{GE} = 0\text{ V}, T_J = 150\text{ }^\circ\text{C}$	-	1.56	1.74	
Gate to emitter leakage current	I_{GES}	$V_{GE} = \pm 20\text{ V}$	-	-	± 250	nA

SWITCHING CHARACTERISTICS ($T_J = 25\text{ }^\circ\text{C}$ unless otherwise specified)						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Total gate charge (turn-on)	Q_g	$I_C = 100\text{ A}$ $V_{CC} = 480\text{ V}$ $V_{GE} = 15\text{ V}$	-	370	555	nC
Gate to emitter charge (turn-on)	Q_{ge}		-	64	96	
Gate to collector charge (turn-on)	Q_{gc}		-	163	245	
Turn-on switching loss	E_{on}	$V_{CC} = 480\text{ V}, I_C = 50\text{ A}, V_{GE} = 15\text{ V},$ $R_g = 5\text{ }\Omega, T_J = 25\text{ }^\circ\text{C},$ energy losses include tail and diode reverse recovery	-	0.7	1.2	mJ
Turn-off switching loss	E_{off}		-	1.7	2.6	
Total switching loss	E_{ts}		-	2.4	3.8	
Turn-on switching loss	E_{on}	$V_{CC} = 480\text{ V}, I_C = 50\text{ A}, V_{GE} = 15\text{ V},$ $R_g = 5\text{ }\Omega, T_J = 125\text{ }^\circ\text{C},$ energy losses include tail and diode reverse recovery	-	1.1	1.7	
Turn-off switching loss	E_{off}		-	2.5	3.8	
Total switching loss	E_{ts}		-	3.6	5.5	
Input capacitance	C_{ies}	$V_{GE} = 0\text{ V}$ $V_{CC} = 30\text{ V}$ $f = 1.0\text{ MHz}$	-	9800	14 700	pF
Output capacitance	C_{oes}		-	602	903	
Reverse transfer capacitance	C_{res}		-	121	182	
Diode junction capacitance	C_t		$V_R = 600\text{ V}, f = 1.0\text{ MHz}$	-	118	
Diode reverse recovery time	t_{rr}	$V_{CC} = 480\text{ V}, I_C = 50\text{ A}$ $di/dt = 200\text{ A}/\mu\text{s}$ $R_g = 5\text{ }\Omega$	-	99	150	ns
Diode peak reverse current	I_{rr}		-	6.5	9.8	A
Diode recovery charge	Q_{rr}		-	320	735	nC
Diode peak rate of fall of recovery during t_b	$dl_{(rec)M}/dt$		-	236	-	A/ μs



THERMISTOR SPECIFICATIONS						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Resistance	$R_0^{(1)}$	$T_0 = 25\text{ }^\circ\text{C}$	-	30	-	$\text{k}\Omega$
Sensitivity index of the thermistor material	$\beta^{(1)(2)}$	$T_0 = 25\text{ }^\circ\text{C}$ $T_1 = 85\text{ }^\circ\text{C}$	-	4000	-	K

Notes

(1) T_0, T_1 are thermistor's temperatures

(2) $\frac{R_0}{R_1} = \exp\left[\beta\left(\frac{1}{T_0} - \frac{1}{T_1}\right)\right]$, temperature in Kelvin

THERMAL AND MECHANICAL SPECIFICATIONS						
PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNITS
Operating junction temperature range	T_J		- 40	-	150	$^\circ\text{C}$
Storage temperature range	T_{Stg}		- 40	-	125	
Junction to case	R_{thJC}	IGBT	-	-	0.28	$^\circ\text{C}/\text{W}$
		Diode	-	-	0.6	
Case to sink per module	R_{thCS}	Heatsink compound thermal conductivity = 1 W/mK	-	0.06	-	
Mounting torque to heatsink $\pm 10\%$		A mounting compound is recommended and the torque should be checked after 3 hours to allow for the spread of the compound. Lubricated threads.	3			Nm
Weight			66			g




Fig. 1 - Typical Load Current vs. Frequency (Load Current = I_{RMS} of Fundamental)




Fig. 2 - Typical Output Characteristics




Fig. 4 - Maximum Collector Current vs. Case Temperature




Fig. 3 - Typical Transfer Characteristics




Fig. 5 - Typical Collector to Emitter Voltage vs. Junction Temperature




Fig. 6 - Maximum Transient Thermal Impedance, Junction to Case (IGBT)




Fig. 7 - Maximum Transient Thermal Impedance, Junction to Case (Diode)




Fig. 8 - Typical Capacitance vs. Collector to Emitter Voltage




Fig. 10 - Typical Switching Losses vs. Gate Resistance




Fig. 9 - Typical Gate Charge vs. Gate to Emitter Voltage




Fig. 11 - Typical Switching Losses vs. Junction Temperature




Fig. 12 - Typical Switching Losses vs. Collector to Emitter Current




Fig. 14 - Maximum Forward Voltage Drop vs. Instantaneous Forward Current




Fig. 13 - Turn-Off SOA




Fig. 15 - Typical Reverse Recovery Time vs. di_F/dt




Fig. 16 - Typical Recovery Current vs. di_F/dt




Fig. 17 - Typical Stored Charge vs. di_F/dt




Fig. 18 - Typical $dI_{(rec)M}/dt$ vs. di_F/dt





Fig. 19 - Electrical diagram

ORDERING INFORMATION TABLE

Device code	50	MT	060	U	LS	T	A	PbF
	1	2	3	4	5	6	7	8


- | | | |
|----------|---|--|
| 1 | - | Current rating (50 = 50 A) |
| 2 | - | Essential part number |
| 3 | - | Voltage rating (060 = 600 V) |
| 4 | - | Speed/type (U = Ultrafast IGBT) |
| 5 | - | Circuit configuration (LS = Low side chopper) |
| 6 | - | Special option: <ul style="list-style-type: none"> • None = No special option • T = Thermistor |
| 7 | - | A = Al ₂ O ₃ DBC substrate |
| 8 | - | PbF = Lead (Pb)-free |

CIRCUIT CONFIGURATION

LINKS TO RELATED DOCUMENTS

Dimensions	www.vishay.com/doc?95175
------------	--

MTP

DIMENSIONS in millimeters



Note

- Unused terminals are not assembled in the package



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.