

TR600-160-R1-B-0.5 Product Details



TR600-160-R1-B-0.5

TE Internal Number: A42758-000

Obsolete

[Contact Product Information Center](#)

PolySwitch Resettable Devices

[Always ELV Compliant \(Find RoHS Compliant Alternates/Statement of Compliance\)](#)

Product Highlights:

- Telecom Application
- Family Name = TR600
- Through Hole Construction
- IH (Room Temperature) = .16 Amps.
- IT (Room Temperature) = .32 Amps.

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [TR600-160-R1-B-0.5](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- UL Recognized = File No. E74889
- CSA File No. = 78165C
- Comment = Devices are available with 0.5 ohm resistance matching.; Designed for equipment required to meet Telcordia GR-1089, UL60950 and TIA968; can be used for ITU applications.

Electrical Characteristics:

- [IH \(Room Temperature\) \(Amps.\)](#) = 0.16
- [IT \(Room Temperature\) \(Amps.\)](#) = 0.32
- [Vmax Operating \(V\)](#) = 250
- [Rmin \(?\)](#) = 4.00
- [Rmax \(?\)](#) = 8.000
- [R1 Max \[Post Trip\] \(?\)](#) = 17.00
- [Vmax Interrupt \(V rms\)](#) = 600
- Power Dissipation (Typical) (W) = 1.00
- R (Typical) (?) = 6.00
- Resistance Matching (?) = 0.5
- UL Rated Voltage (V) = 250

Termination Related Features:

- Construction = Through Hole

Body Related Features:

- Lead Type = Kinked

Contact Related Features:

- Family Name = TR600

Configuration Related Features:

- Coating = Coated

Industry Standards:

- [RoHS/ELV Compliance](#) = ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was ELV compliant

Conditions for Usage:

- [Operating Temperature \(Max.\) \(°C\)](#) = 85

Operation/Application:

- Application = Telecom

Packaging Related Features:

- Packaging Method = Bulk, Tape & Reel

Other:

- Brand = Raychem