



- NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
1. BRASS PER QQ-B-626
 2. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 3. BERYLLIUM COPPER PER QQ-C-530
 4. GOLD PL. 3 MIN THICK OVER NICKEL PL. 100 MIN THICK OVER COPPER STRIKE
 5. GOLD PL. 50 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 6. TEFLON MIL-P-19468
 7. JIS H 3250, C 2700

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO
9	NUT			1	RN108-9-05X23S
8	FERRULE			1	FR-39/32X95
7	NUT			1	15687061606-5
6	INSULATOR	DELRIN	NATURAL	1	15687061606-4
5	CONTACT PIN			1	1566412A1-003-5
4	INSULATOR		NATURAL	1	1566412A1-003-4
3	INSULATOR		NATURAL	1	1566412A1-3-B
2	BODY			1	1566412A1-2-27/17
1	OUT CONTACT			1	1566412A1-003-1

DIMENSIONS ARE IN MILLIMETERS				PART NO.			
UNLESS OTHERWISE SPECIFIED TOLERANCES				1566412A1-003-N/3GT50G-75			
				APPROVED	DATE		
				CHECKED	DATE		
				DRAWN	DATE		
SCALE	2/1	ISSUE	A	FILE NO			

Amphenol	
TITLE 1.6-5.6 R/A CRIMP JACK (FOR RG-179U, 187A/U CABLE)	
DRAWING NO. KJ-1566412A1-003-N/3GT50G-75	
ITEM NO.	