

## EPC3095-X


- Split Bobbin Construction
- Dual Primaries : 115 V / 230 V
- UL 94V-0 Recognized Components
- UL 1446 Class B Insulation System
- Meets or exceeds CSA/TUV/VDE Specifications for Creepage, Clearance and Dielectric Strength

### Electrical Parameters @ 25° C


Part Number	Primary Voltage		Secondary Voltage		Secondary Current (A-Rms)		Power Rating (VA)
	Parallel Connection	Series Connection	Parallel Connection	Series Connection	Parallel Connection	Series Connection	
EPC3095-1	115	230	5.0	10	0.22	0.11	1.1
EPC3095-2	115	230	6.3	12.6	0.58	.09	1.1
EPC3095-3	115	230	8.0	16	0.14	0.7	1.1
EPC3095-4	115	230	10	20	0.11	0.55	1.1
EPC3095-5	115	230	12	24	0.09	0.45	1.1
EPC3095-6	115	230	14	28	0.08	0.04	1.1
EPC3095-7	115	230	18	36	0.06	0.03	1.1
EPC3095-8	115	230	24	48	0.046	0.023	1.1
EPC3095-9	115	230	28	56	0.04	0.02	1.1
EPC3095-10	115	230	60	120	0.02	0.01	1.1

• Switching Frequency : 50 Hz - 500 Hz • Isolation : 2500 Vrms •

### Package



### Schematic



Note :  
1. Optional Mounting Screws and Nut : None

Unless Otherwise Specified Dimensions are in Inches /mm ± .010 / .25