

Build-Out Optical Attenuators, FC

FC, 15 dB

CORNING

Corning universal build-out optical attenuators are used to interconnect single-mode connectors with or without attenuation. The FC attenuator styles are available in 0-16, 18 and 20 dB levels. Each build-out attenuator requires the use of a build-out block (sold separately) that replaces the standard adapter. The unique design of these attenuators allows for easy change-out of attenuation values with no tools required, and the 0 dB offering is very useful for connections where no additional attenuation is required.

Features and Benefits

Dual-wavelength design

Operable at 1310 and 1550 nm

Easy change-out of attenuation values

No tools required

Single-mode precision sleeve

Provides precise alignment



Part Number: ATN-54U-BO-15



Part Number: ATN-54U-BO-15

CORNING

Build-Out Optical Attenuators, FC

FC, 15 dB

CORNING

Specifications

General Specifications

Attenuator Type	Build-Out
Product Type	Attenuators
Compatibility	FC
Packaging	Single Pack

Temperature Range

Operation	-40 °C to 65 °C (-40 °F to 149 °F)
-----------	------------------------------------

Design - Connector

Housing Material	Composite
------------------	-----------

Optical Specifications - Connector

Attenuation	15 dB
Attenuation Tolerance	± 2.25 dB
Reflectance	≤ -40 dB

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Ordering Information

Part Number	ATN-54U-BO-15
Product Description	FC Build-Out Optical Attenuator

Shipping Information

Units per Delivery	1/1
Package Contents	Attenuator, FC

Build-Out Optical Attenuators, FC

FC, 15 dB

CORNING

Notes



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2014 Corning Optical Communications. All rights reserved.

CORNING