

# TWO-PIN POLARIZED 30/330 SERIES TWBNC/TWTNC Mil-C-3655 Interface

**CABLE PLUG**  
TWTNC POSITIVE ALIGNING  
TWO-PIN POLARIZED

**PLPA330-** ⚠

**CIRCUIT BOARD BULKHEAD JACK**  
RIGHT ANGLE-TWO-PIN  
POLARIZED TWINAX (TWBNC)

Mounting Hole: D3.125

**CBBJR39A**

**CABLE PLUG**  
WRENCH CRIMP, TWO-PIN POLARIZED

2-lug Threaded

**PL30-** ⚠  
**PL330-** ⚠

**Bulkhead Jack BJ30 Shown**

**Bulkhead Jack BJ31 Shown**

**Bulkhead Jack BJ30 Shown**

2-lug Threaded

Mounting Hole: D5.130

**BJ30**  
**BJ330**

**FEED-THROUGH JACK**  
TWO-PIN POLARIZED

2-lug Threaded

Mounting Hole: D3.160

**BJ38**  
**BJ338**

**Bulkhead Cable Jack BJ39**

2-lug Threaded

Mounting Hole: D3.218

**BJ39-** ⚠  
**BJ339-** ⚠

⚠ - Refers to Cable Group Table, see pages 68-88. "D" mounting holes are on page 45. Note: Only 30/330 Series have two-pin polarizations.