

SRMB2.5/18-FW1-18E

- 36 Connections
- Direct mounting
- With one-sided label





Phoenix Mecano Brand

Technical Data

Wire sizes		Insulating Material	
Solid min	0.2 mm ²	Material	PA 6.6
Solid max	4.0 mm ²	Flammability Class	UL 94 V-2
Stranded (flexible) min	0.2mm ²	Temperatures	
Stranded (flexible) max	4.0 mm ²	Working Temperature	-40 - 105 °C
Stranded with Ferrule min	0.2 mm ²	Dimensions	
Stranded with Ferrule max	2.5 mm ²	Stripped Length	7.0 mm
Clamping Range min	0.2mm ²	Width	5.0 mm
Clamping Range max	4.0 mm ²	Height	23.0 mm
		Length	106.2 mm
		Length Hole Direct Mounting	99.1 mm

Colours

-  BEIGE, similar RAL 1019
-  BLUE, similar RAL 5015

Connection Diagram



Order Data

Article Designation	Article Number	PU
SRMB2.5/18-FW1-18E-BEIGE	41348.2	20
SRMB2.5/18-FW1-18E-BLUE	41348.5	20

Accessoires

Article Designation	Article Number	PU
External Cross-Connector insulated AQI2/5/11	492032.0	50
External Cross-Connector insulated AQI3/5/11	492033.0	50
External Cross-Connector insulated AQI4/5/11	492044.0	10
External Cross-Connector insulated AQI10/5/11	492045.0	10

Ratings

Ratings	UR		IEC
	Rated Voltage	300 V	300 V
Rated Current	20 A	20 A	24 A
Rated Wire Size	AWG 22-12	AWG 22-12	2.5 mm ²
Rated Impulse Voltage			6 V
Pollution Degree			3