

HIGH FREQUENCY DIL 14 VCXO DFV 14-MLECP (3.3 V)

KEY FEATURES


622 to 800 MHz

Parametric frequency multiplication


0.4 ps RMS jitter over 50 kHz to 80 MHz B.W.

APPLICATIONS

OC-192/Sonet/SDH



H = 8.50 mm



Function	DFV 14
V control	1
GND	7
Output 1	8
Output 2	9
Vcc	14

TYPE	DFV 14-MLECP
Frequency Range	622 to 800 MHz
Standard Frequencies	622.0800; 644.5313; 666.5143; 669.3266; 693.4828; 777.6000 MHz

ELECTRICAL SPECIFICATIONS	
supply voltage	3.3 V ± 5 %
supply current (no load)	≤ 60 mA
output load	LVPECL 100 K (50 Ω to 1.3 V)
duty cycle @ 50% level	45/55...55/45 %
rise/fall times (20 to 80%)	≤ 0.5 ns
high/low levels	≥ 2.22 V / ≤ 1.7 V
jitter RMS (12 kHz to 5 MHz)	0.08 ps typ; ≤ 0.10 ps
jitter RMS (12 kHz to 20 MHz)	0.12 ps typ; ≤ 0.15 ps
jitter RMS (50 kHz to 80 MHz)	0.32 ps typ; ≤ 0.40 ps
complementary output on pin 9	180° phase shifted
start up	≤ 10 ms @ 3.15 V

FREQUENCY STABILITY			detailed tolerances [ppm]						
type	temperature range	model code	stability versus:				pulling range positive function	control voltage	
			temp.	@ 25°C	Vcc	load			ageing
DFV 14-MLECP	0 to 70°C	100B20	≤ ± 20	≤ ± 10	≤ ± 3	≤ ± 0.5	≤ ± 2	≥ ± 100	1.65 V ± 1.35 V
		100B25	≤ ± 25						
		100B50	≤ ± 50						
	-40 to 85°C	100E30	≤ ± 30						
remarks			input impedance ≥ 10 kΩ, modulation bandwidth ≥ 10 kHz @ -3dB ageing is 1 st year at 25°C						

ORDERING CODE	type + option code + frequency + model code
Example	DFV 14-MLECP 622.08 MHz 100B20