


T-43-15

54/7486
54S/74S86
54LS/74LS86

QUAD 2-INPUT EXCLUSIVE-OR GATE

CONNECTION DIAGRAM
PINOUT A



ORDERING CODE: See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0 V \pm 5\%$, $T_A = 0^\circ C$ to $+70^\circ C$	$V_{CC} = +5.0 V \pm 10\%$, $T_A = -55^\circ C$ to $+125^\circ C$	
Plastic DIP (P)	A	7486PC, 74S86PC 74LS86PC		9A
Ceramic DIP (D)	A	7486DC, 74S86DC 74LS86DC	5486DM, 54S86DM 54LS86DM	6A
Flatpak (F)	A	7486FC, 74S86FC 74LS86FC	5486FM, 54S86FM 54LS86FM	3I

INPUT LOADING/FAN-OUT: See Section 3 for U.L. definitions

PINS	54/74 (U.L.) HIGH/LOW	54/74S (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
Inputs	1.0/1.0	1.25/1.25	1.0/0.375
Outputs	20/10	25/12.5	10/5.0 (2.5)

DC AND AC CHARACTERISTICS: See Section 3*

SYMBOL	PARAMETER	54/74		54/74S		54/74LS		UNITS	CONDITIONS
		Min	Max	Min	Max	Min	Max		
I _{CC}	Power Supply Current	XM		43	75	10	10	mA	V _{CC} = Max, V _{IN} = Gnd
		XC		50	75	10	10		
t _{PLH}	Propagation Delay	23	3.5	10.5	12	ns	Other Input LOW Figs. 3-1, 3-5		
t _{PHL}		17	3.0	10	17				
t _{PLH}	Propagation Delay	30	3.5	10.5	13	ns	Other Input HIGH Figs. 3-1, 3-4		
t _{PHL}		22	3.0	10	12				

*DC limits apply over operating temperature range; AC limits apply at T_A = +25°C and V_{CC} = +5.0 V.